

SMOKE DETECTOR TESTER

MSDS Number

BBFLC

National Stock Number

6350-00D001776

Product Name

SMOKE DETECTOR TESTER

Manufacturer

AEROSOL SERVICES COMPANY INC

Product Identification

Product ID:SMOKE DETECTOR TESTER

MSDS Date:01/01/1987

FSC:6350

NIIN:00D001776

MSDS Number: BBFLC

Responsible Party

AEROSOL SERVICES COMPANY,INC.

425 S. NINTH AVE

CITY OF INDUSTRY , CA 91746-3314

US

Emergency Phone: 213-968-8531

Info Phone: 213-968-8531

Cage: 7K742

Contractor

DIRECT SAFETY CO,DIV OF JENSEN TOOLS INC

PHOENIX, AZ 85044-5399

US

602-968-7009

Cage: 2P651

Ingredients

PETROLEUM HYDROCARBON

Fraction By Weight: 10%.

CHLORINATED HYDROCARBON

Fraction By Weight: 15%.

ESTER

Fraction By Weight: 5%.

HYDROCARBON AEROSOL PROPELLANTS

Fraction By Weight: 70%.

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:INHAL: IRRITATION, DIZZINESS, HEADACHE,
UNCONSCIOUSNESS, ASPHYXIATION; SKIN: DRYNESS & DEFATTING OF SKIN
W/EXCESS LIQUID CONTACT; EYES: IRRITATES

First Aid

First Aid:INHAL: REMOVE FROM AREA. GIVE CPR/O*2 AS SITUATION DICTATES.
GET MED. ATTN.; SKIN: WASH W/WARM SOAP & WATER. REMOVE CONTAMINATED
CLOTHING; EYES: FLUSH W/CLEAR WATER FOR 15 MIN. OR UNTIL IRRITATION
SUBSIDES. GET MED. ATTN. INGEST: GIVE TWO GLASSES OF WATER. INDUCE
VOMITING IMMEDIATELY BY STICKING FINGER DOWN THROAT. NEVER GIVE AN
UNCONSCIOUS PERSON ANYTHING BY MOUTH.

Fire Fighting

Flash Point:N/R FOR AEROSOL
Lower Limits:9.5
Upper Limits:1.8
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, & FOAM
Fire Fighting Procedures:MFR CITES NONE
Unusual Fire/Explosion Hazard:RUPTURE OF CONTAINER ABOVE 130F COULD
CAUSE BOILING LIQUID FLASH FIRE IF IGNITED.

Accidental Release

Spill Release Procedures:LEAKING CANS SHOULD BE PLACED IN OPEN PAIL
OUTDOORS UNTIL PRESSURE HAS DISSIPATED, THEN DISPOSE OF.

Handling

Handling and Storage Precautions:KEEP FROM SOURCES OF IGNITION. DO NOT
TAKE INTERNALLY. AVOID EXCESSIVE INHALATION OF AEROSOL. DO NOT
STORE ABOVE 120F.
Other Precautions:DO NOT INCINERATE OR PUNCTURE CONTAINER.

Exposure Controls

Respiratory Protection:NONE NEEDED UNDER NORMAL CONDITIONS OF USE.
Ventilation:SUFFICIENT TO KEEP SOLVENT VAPOR BELOW TLV.
Protective Gloves:NONE
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Work Hygienic Practices:AVOID EXCESSIVE INHALATION OF AEROSOL.
Supplemental Safety and Health
MSDS RCVD:6NOV87.

Chemical Properties

HCC:V3
Vapor Pres:50PSIG(70F)
Vapor Density:> 1.
Spec Gravity:0.98
Solubility in Water:INSOLUBLE
Appearance and Odor:AEROSOL AIR SPRAY
Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HIGH TEMPERATURES
Hazardous Decomposition Products:MFR REPORTS: "NONE"
Conditions to Avoid Polymerization:WILL NOT POLYMERIZE

Disposal

Waste Disposal Methods:BURY AT APPROVED LANDFILL IAW LOCAL, STATE, AND
FEDERAL LAWS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.