

825X3888(MANUF. CODE ID)

MSDS Number

BBFQM

National Stock Number

8010-00F000000

Product Name

825X3888(MANUF. CODE ID)

Manufacturer

DESOTO INC

Product Identification

Product ID:825X3888(MANUF. CODE ID)

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000000

MSDS Number: BBFQM

Responsible Party

DESOTO, INC.

Emergency Phone: 312/391-9000

Cage: 32758

Contractor

DESOTO, INC.

5030

DES PLAINES, IL 60017

US

708-391-9000

Cage: 32758

Ingredients

ORGANIC TIN COMPOUND

Fraction By Weight:

OSHA PELS, 0.1 MG/M3 (SN)

ACGIH TLV: S, 0.1 MG/M3 (SN)

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 10%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ETHYL ACETATE (SARA III)

CAS: 141-78-6

RTECS: AH5425000

Fraction By Weight: 5%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 20%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 10%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:INHALATION-ANESTHETIC;HEADACHE, DIZZINESS,
CONFUSION UNCONSCIOUSNESS OR COMA

First Aid

First Aid:EYES-FLUSH WITH WATER;SKIN-WASH WITH WATER; INHALATION-REMOVE
FROM EXPOSURE, RESTORE BREATHING, KEEP WARM AND QUIET, NOTIFY
PHYSICIAN; INGESTION-CONSULT A PHYSICIAN. REMOVE
CONTAMINATED CLOTHING.

Fire Fighting

Flash Point:22.0F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:USE FOG NOZZLES IF USING WATER, WEAR
SELF-CONT BREATH. APPR

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND
NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F, STORE IN
BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLE LIQUIDS.

Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED
WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

Exposure Controls

Respiratory Protection:ORGANIC VAPOR RESPIRATOR, AIRLINE TYPE
RESPIRATORS IN CONFINED AREAS
Ventilation:GENERAL DILUTION, OR LOCAL TO KEEP TLV BELOW LIMIT.
Protective Gloves:BUTYL RUBBER
Eye Protection:SPLASH-PROOF GOGGLES
Other Protective Equipment:PROTECTIVE CLOTHING(BUTYL, NEOPRENE OR
NITRILE RUBBER APRON)
Supplemental Safety and Health
MEHTYL ETHYL KETONE SILICA-AMORPHOUS 10%.

Chemical Properties

Boiling Pt:B.P. Text:171-313F
Evaporation Rate & Reference:SLOWER(ETHER=1)
Percent Volatiles by Volume:62.3

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FED
REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.