



F63 W 12

MSDS Number

BBFRP

National Stock Number

8010-00F000019

Product Name

F63 W 12

Manufacturer

THE SHERWIN WILLIAMS COMPANY

Product Identification

Product ID:F63 W 12 MSDS Date:01/01/1985 FSC:8010 NIIN:00F000019 MSDS Number: BBFRP

Responsible Party

THE SHERWIN-WILLIAMS COMPANY Emergency Phone: 216/566-2917

Cage: DO693

Contractor

THE SHERWIN-WILLIAMS CO

CLEVELAND, OH 44115

216-566-2902

US

Cage: DO693

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5 - 10% OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7 RTECS: ZE2100000 Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS





METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000 Fraction By Weight:

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

CYCLOHEXANONE (SARA III)

CAS: 108-94-1

RTECS: GW1050000

Fraction By Weight: 25%

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293 EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 10%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: HIGH CONC OF VAPORS IN CONFINED AREA ARE ANESTHETIC. LIGHTHEADEDNESS, OR STAGGERING GAIT.

First Aid

First Aid:REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. EYES-FLUSH WITH LARGE QUANT. OF WATER FOR 15 MIN. SKIN-WASH AFFECTED AREA WITH WATER. REMOVE CONTAMINATED CLOTHING ANDWASH BEFORE REUSE.

Fire Fighting

Flash Point:41F PMCC Lower Limits:1.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: FULL PROTECTIVE EQUIPMT, INCL SELF-CONT.

BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. SPEC PRECAUTION FOR APPLIC TO HOT SURFCE

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.





Handling

Handling and Storage Precautions: CONTENTS ARE FLAMMABLEKEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. DO NOT SMOKE, KEEP AIR VENTATED, EXTINGUISH ALL SOURCES OF IGNITION.

Other Precautions: AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. KEEP CONTAINER CLOSED WHEN NOT IS USE. DO NOT TRANSF CONTENTS TO OTHER CONTAINERS FOR STORAGE.

Exposure Controls

Respiratory Protection: POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IS PREFERRED.

Ventilation: LOCAL EXHAUST IF PREFERABLE. MECHANICAL IS ACCEPTABLE.

Protective Gloves: REQUIRED

Eye Protection: SIDE SHIELDED GOGGLES

Other Protective Equipment: CONSULT NFPA CODE. USE APPROVED BONDING AND

GROUNDING.

Supplemental Safety and Health

PIGMENTED COMPONENT FOR 2-PACKAGE POLYURETHANE COATING. ADDRESS-101

PROSPECT AVENUE N.W. CLEVELAND, OH 44115

Chemical Properties

Boiling Pt:B.P. Text:174-313F

Vapor Density:>AIR

Evaporation Rate & Reference: Percent Volatiles by Volume: 68

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE, CARBON MONOX
IDE, HYDROGEN CHLORIDE

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.