



---

## **SCREEN WASH**

### **MSDS Number**

BBFVG

### **National Stock Number**

6850-00F000082

### **Product Name**

SCREEN WASH

### **Manufacturer**

NAZ DAR COMPANY

### **Product Identification**

Product ID: SCREEN WASH

MSDS Date: 01/01/1987

FSC: 6850

NIIN: 00F000082

MSDS Number: BBFVG

### **Responsible Party**

NAZ DAR COMPANY

Emergency Phone: 943-8338

Cage: DO971

### **Contractor**

NAZDAR COMPANY

CHICAGO, IL 60622-4292

US

312-943-8338; 800-736-7636

Cage: 76708

### **Ingredients**

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 50%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 50%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS



## Hazards

Effects of Overexposure: INHALATION-ANESTHETIC. IRRITATION OF RESPIRATORY TRACT, ACUTE NERVOUS SYSTEM DEPRESSION.

## First Aid

First Aid: FUMES-REMOVE FROM EXPOSURE, RESTORE BREATHING. NOTIFY PHYSICIAN. EYES-FLUSH WITH LARGE AMTS OF WATER FOR 15 MINUTES. SKIN-REMOVE WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.

## Fire Fighting

Flash Point: 0°F TCC  
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL OR FOAM  
Fire Fighting Procedures: WATER MAY BE USED TO COOL CLOSED CONTAINERS  
Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE INERT SORBENT AND NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120°F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS 1 FLAMMABLE LIQUIDS.  
Other Precautions: DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT FLAME CUT, BRAZE, OR WELD WITHOUT APPROVED RESPIRATOR/VENTILATION.

## Exposure Controls

Respiratory Protection: MECHANICAL FILTER  
RESPIRATOR/CHEMICAL-MECHANICAL RESPIRATOR  
Ventilation: GENERAL DILUTION OR LOCAL EXHAUST TO KEEP BELOW TLV  
Protective Gloves: RECOMMENDED  
Eye Protection: SPLASH SAFETY EYEWEAR  
Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING  
Supplemental Safety and Health  
1097 N. NORTH BRANCH STREET, CHICAGO, ILLINOIS 60622.

## Chemical Properties

Boiling Pt: B.P. Text: 133-284°F  
Vapor Density: >AIR  
Evaporation Rate & Reference: Percent Volatiles by Volume: 100

## Stability

Stability Indicator/Materials to Avoid: YES  
VERY STRONG OXIDIZING AGENTS  
Stability Condition to Avoid: VERY STRONG OXIDIZING AGENTS  
Hazardous Decomposition Products: CARBON MONOXIDE OR NITROGEN OXIDES

## Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.