

## **MIL-C-46168B WHITE 37875**

### **MSDS Number**

BBFVW

### **National Stock Number**

8010-00F000091

### **Product Name**

MIL-C-46168B WHITE 37875

### **Manufacturer**

EVERSEAL MANUFACTURING CO INC

### **Product Identification**

Product ID:MIL-C-46168B WHITE 37875

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000091

MSDS Number: BBFVW

### **Responsible Party**

EVERSEAL MANUFACTURING CO., INC.

Emergency Phone: 201/943-4986

Cage: EO432

### **Contractor**

EVERSEAL MFG CO INC

RIDGEFIELD, NJ 07657-2329

US

201-943-4986

Cage: 72988

### **Ingredients**

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 30%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 5 - 10%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

### **Hazards**

Effects of Overexposure:BREATHING VAPOR CAN CAUSE IRRITATION OF NOSE,

THROAT, HEADACHE, NAUSEA, VOMITING, LEAD POISONING

## First Aid

First Aid: REMOVE TO FRESH AIR AND CALL A PHYSICIAN. WASH AFFECTED AREAS WITH WATER. IF SWALLOWED PUMP OUT STOMACH AND CALL PHYSICIAN.

## Fire Fighting

Flash Point: 34F SETA

Lower Limits: 1.4

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL FOR SMALL FIRES; FOAM-LARGE FIRE

Fire Fighting Procedures: HANDLE AS FLAMMABLE LIQUID, WEAR RESPIRATORY PROTECTION

## Accidental Release

Spill Release Procedures: FLUSH WITH LARGE QUANTITIES OF WATER. ELIMINATE SOURCES OF IGNITION.

## Handling

Handling and Storage Precautions: STORE IN CLEAN DRY AREA. AVOID HEAT OR SPARKS. KEEP AWAY FROM FLAME. RNING.

FLAMMABLE-BREATHING OF VAPOR MAY BE HARMFUL

Other Precautions: LIQUID MAY CAUSE IRRITATION-KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME, KEEP CONTAINER CLOSED. AVOID CONTACT WITH EYES. IN SE OF CONTACT IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES.

## Exposure Controls

Respiratory Protection: ORGANIC VAPOR MASK WITH DUST CATCHING ABILITY = BM 2158

Ventilation: LOCAL EXHAUST WITH DUST COLLECTOR

Protective Gloves: YES

Eye Protection: YES

Other Protective Equipment: IMPERMEABLE COVER WHERE EXPOSED TO SPLASH.

Supplemental Safety and Health

475 BROAD AVENUE-RIDGEFIELD, NEW JERSEY 07657.

## Chemical Properties

Boiling Pt: B.P. Text: 153-244F

Vapor Pres: 2

Vapor Density: 1

Spec Gravity: 1.56

Evaporation Rate & Reference: 1

Solubility in Water: NO

Percent Volatiles by Volume: 59

## Stability

Stability Indicator/Materials to Avoid: YES

AVOID HEAT & ORGANIC MATTER

Stability Condition to Avoid: IN PRESENCE OF HEAT & ORGANIC MATTER, LEAD CHROMATE IGNITES

## Disposal

Waste Disposal Methods: SWEEP UP RESIDUE AND DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.