

APCO 1260HS PART C TOPCOAT

MSDS Number

BBFYQ

National Stock Number

8010-00F000145

Product Name

APCO 1260HS PART C TOPCOAT

Manufacturer

APPLIED PLASTICS CO INC

Product Identification

Product ID:APCO 1260HS PART C TOPCOAT

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000145

MSDS Number: BBFYQ

Responsible Party

APPLIED PLASTICS CO., INC.

Emergency Phone: 213/322-8050

Cage: 05866

Contractor

APPLIED PLASTICS CO

EL SEGUNDO, CA 90245

US

Cage: 05866

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 98%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ORGANIC TIN COMPOUND

Fraction By Weight: 2%

OSHA PELs, 0.1 MG/M3 (SN)

ACGIH TLV: S, 0.1 MG/M3 (SN)

Hazards

Effects of Overexposure:MAY CAUSE ANESTHESIA AND STRONG SKIN IRRITATION.

First Aid

First Aid:EYES: FLUSH WITH COPIOUS AMOUNTS OF WATER. SEEK MEDICAL AID.

SKIN: WASH THOROUGHLY WITH SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. IF SEVERE SYMPTOMS DEVELOP SEEK MEDICAL AID. INGESTION: SEEK MEDICAL AID IF UNUSUAL SYMPTOMS DEVELOP.

Fire Fighting

Flash Point: 79F T.C.C.

Lower Limits: 1.1

Upper Limits: 7.0

Extinguishing Media: CO2 OR DRY CHEMICAL

Fire Fighting Procedures: NONE

Unusual Fire/Explosion Hazard: NONE

Accidental Release

Spill Release Procedures: VENTILATE AREA. SOAK UP IN ABSORBANT, CONTAIN.

Handling

Handling and Storage Precautions: FOR INDUSTRIAL USE ONLY. WARNING. MAY CAUSE SKIN IRRITATION. HARMFUL IF INHALED. AVOID SKIN CONTACT. IF CONTACT OCCURS WASH WITH SOAP & WATER.

Other Precautions: AVOID BREATHING VAPOR. USE ADEQUATE VENTILATION. SPI CLASSIFICATION 2. KEEP AWAY FROM HEAT, SPARKS AND FIRE. DO NOT LEAVE CONTAINER OPEN.

Exposure Controls

Respiratory Protection: HYDROCARBON VAPOR CARTRIDGE RESPIRATOR.

Ventilation: SUFFICIENT TO MAINTAIN TLV < OR = 100PPM & 0.1MG/M3

Protective Gloves: HYDROCARB. RESISTANT

Eye Protection: SAFETY GLASSES/SIDE SHIELD

Supplemental Safety and Health

612 E. FRANKLIN AVE., EL SEGUNDO, CALIF. 90245.

Chemical Properties

Boiling Pt: B.P. Text: 277F

Vapor Pres: 10

Vapor Density: 3.66

Spec Gravity: 0.86

Evaporation Rate & Reference: Solubility in Water: INSOLUBLE

Appearance and Odor: WATER WHITE THIN LIQUID-XYLENE ODOR

Percent Volatiles by Volume: 98

Stability

Stability Indicator/Materials to Avoid: NO

O2 AND STRONG OXIDANTS.

Stability Condition to Avoid: HIGH TEMPERATURES OR HEAT

Hazardous Decomposition Products: INCOMPLETE COMBUSTION PRODUCES CO.

Disposal

Waste Disposal Methods: STANDARD INDUSTRIAL FLAMMABLE LIQUID DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.