



---

## **ENPOX CATALYST CL.A THNR. ADCT. CONC. T622**

### **MSDS Number**

BBFY

### **National Stock Number**

8010-00F000150

### **Product Name**

ENPOX CATALYST CL.A THNR. ADCT. CONC. T622

### **Manufacturer**

PRATT AND LAMBERT

### **Product Identification**

Product ID: ENPOX CATALYST CL.A THNR. ADCT. CONC. T622

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00F000150

MSDS Number: BBFY

### **Responsible Party**

PRATT & LAMBERT

Emergency Phone: 316/733-1361

Cage: 06020

### **Contractor**

PRATT & LAMBERT

Cage: 06020

### **Ingredients**

2,4,6-TRI(DIMETHYLAMINOMETHYL) PHENOL

CAS: 90-72-2

RTECS: SN3500000

Fraction By Weight:

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 15 - 20%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS



DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 25%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

## Hazards

Effects of Overexposure: INHALATION: ANESTHETIC. IRRITATION OF NOSE, THROAT, EYES AND POSSIBLE DIZZINESS AND NAUSEA.

## First Aid

First Aid: INHALATION: REMOVE FROM EXPOSURE AND PROVIDE FRESH AIR. SPLASH(EYES): FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER. SKIN: REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH WATER. INGESTION: DO NOT INDUCE VOMITING. CONSULT MD IN ALL CASES.

## Fire Fighting

Flash Point: 44F T.C.C  
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, OR ALCOHOL FOAM  
Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE  
Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES IF IGNITION. VENTILATE AREA AND AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND USE NON-SPARKING TOOLS. STEPS MUST BE TAKEN TO AVOID CONTAMINATION OF GROUND WATER STREAMS.

## Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 1910.106. CONTAINERS SHOULD BE BONDED TOGETHER WHEN TRANSFERRING CONTENTS.  
Other Precautions: DO NOT CUT OR WELD ON EMPTY CONTAINERS. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS AND MIXING DIRECTIONS HAVE BEEN READ AND FULLY UNDERSTOOD BY THE USER.

## Exposure Controls

Respiratory Protection: MECHANICAL RESPIRATOR TO REMOVE OVERSPRAY  
Ventilation: GENERAL DILUTION OR LOCAL EXHAUST  
Protective Gloves: SOLVENT IMPERMEABLE  
Eye Protection: SAFETY EYEWEAR  
Other Protective Equipment: PROPER PERSONAL EQUIPMENT TO PREVENT SKIN CONTACT  
Supplemental Safety and Health  
630 EAST 13TH ANDOVER, KANSAS 67002.

## Chemical Properties

Boiling Pt: B.P. Text: 175-283F  
Vapor Density: > AIR  
Evaporation Rate & Reference: Percent Volatiles by Volume: 100

## Stability

Stability Indicator/Materials to Avoid: YES  
STRONG ACIDS OR ALKALIS.  
Stability Condition to Avoid: AVOID FIRES, HEAT, SPARKS AND HOT SURFACES.



Hazardous Decomposition Products:SMOKE & OXIDES OF NITROGEN AND CARBON WHEN BURNED.

Conditions to Avoid Polymerization:DRIERS OR REACTIVE CHEMICALS W/OUT TECHNICAL SUPERVISION.

## **Disposal**

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN EPA APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.