

FIRESTONE 95195 CEMENT

MSDS Number

BBFZH

National Stock Number

8040-00F000157

Product Name

FIRESTONE 95195 CEMENT

Manufacturer

AM FUEL AMERICIAN FUEL AND COATED FABRICS COMPANY

Product Identification

Product ID:FIRESTONE 95195 CEMENT

MSDS Date:01/01/1985

FSC:8040

NIIN:00F000157

MSDS Number: BBFZH

Responsible Party

AM FUEL AMERICIAN FUEL AND COATED FABRICS COMPANY

Emergency Phone: 501/234-3381

Cage: 05476

Contractor

AM FUEL AMERICIAN FUEL AND COATED FABRICS COMPANY

Cage: 05476

Ingredients

PIGMENTS, UNSPECIFIED

Fraction By Weight: 9.0%

LEAD MONOXIDE (LEAD OXIDE YELLOW)

CAS: 1317-36-8

RTECS: OG1750000

Fraction By Weight: 1.0%

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.15 MG/M3(PB); 8990

VEHICLE, UNSPECIFIED

Fraction By Weight: 13%

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 77%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: INHALATION: IRRITATION OF NOSE & THROAT, HEADACHE, VOMITING & UNCONSCIOUSNESS; IRRITATION OF EYES.

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR AND CALL A PHYSICIAN. SKIN: WASH PROMPTLY WITH SOAP AND WATER. EYES: WASH IMMEDIATELY WITH A GENTLE STREAM OF WATER FOR AT LEAST 15 MINUTES.

Fire Fighting

Flash Point: 16F, 28.4C, T.O.C

Lower Limits: 1.8

Upper Limits: 11.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, OR FOAM

Fire Fighting Procedures: DO NOT USE SOLID STREAM OF WATER

Unusual Fire/Explosion Hazard: NONE

Accidental Release

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. AVOID BREATHING OF VAPORS. ABSORB ON VERMICULITE, RY SAND, EARTH OR SIMILAR MATERIAL AND DISPOSE OF IN ACCORDANCE WITH GOVNMNT REGULATIONS.

Handling

Handling and Storage Precautions: PROVIDE ADEQUATE VENTILATION. STORE IN A COOL, DRY AREA.

Exposure Controls

Respiratory Protection: CHEMICAL CARTRIDGE RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE

Ventilation: LOCAL EXHAUST PREFERRED

Protective Gloves: RUBBER

Eye Protection: SPLASH-PROOF GOGGLES

Other Protective Equipment: NONE

Supplemental Safety and Health

P.O. BOX 887 MAGNOLIA, AR. 71753.

Chemical Properties

Boiling Pt: B.P. Text: 174-176F

Vapor Pres: 71

Vapor Density: 2.41

Spec Gravity: 0.805

Evaporation Rate & Reference: 4.6

Solubility in Water: SLIGHT

Appearance and Odor: VISCOUS, BLACK LIQUID WITH KETONE-LIKE ODOR

Percent Volatiles by Volume: 83.3

Stability

Stability Indicator/Materials to Avoid: YES

CONTACT WITH STRONG OXIDIZING AGENTS

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: THERMAL DECOMPOSITION MAY PRODUCE CARBON MONOXIDE/DIOXIDE

Disposal

Waste Disposal Methods: IN ACCORDANCE WITH GOVERNMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.