

## **PRO-SEAL 899 CLASS A (BASE)**

### **MSDS Number**

BBGBQ

### **National Stock Number**

8030-00F000183

### **Product Name**

PRO-SEAL 899 CLASS A (BASE)

### **Manufacturer**

ESSEX CHEMICAL CORP

### **Product Identification**

Product ID:PRO-SEAL 899 CLASS A (BASE)

MSDS Date:01/01/1987

FSC:8030

NIIN:00F000183

MSDS Number: BBGBQ

### **Responsible Party**

ESSEX CHEMICAL CORPORATION

19451 SUSANA ROAD

COMPTON , CA 90221

Emergency Phone: (213) 537-7600

Info Phone: (213) 537-7600

Cage: 83527

### **Contractor**

ESSEX CHEMICAL CORP PRO-SEAL DIV

COMPTON, CA 90221-5713

US

310-537-7600

Cage: 83527

### **Ingredients**

MODIFIERS

Fraction By Weight: 0-5%

INERT FILLERS

Fraction By Weight: 25-35%

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 17%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

POLYSULFIE RESINS

Fraction By Weight: 60-65%

## Hazards

LD50 LC50 Mixture:ORAL LD50 RATS 0.5 TO 5G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN/EYE: MAY CAUSE IRRITATION.

INHALATION: NARCOTIC EFFECT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN/EYE: MAY CAUSE IRRITATION. INHALATION:  
NARCOTIC EFFECT.

## First Aid

First Aid:SKIN: WASH AFFECTED AREAS COPIOUSLY W/WATER. INHALATION:  
REMOVE TO FRESH AIR. INGESTION: GIVE EMETIC. CONSULTY PHYSICIAN.

## Fire Fighting

Flash Point Method:TCC

Flash Point:41F

Lower Limits:1.3%

Upper Limits:6.8%

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:FLAMMABLE MATERIAL.

## Accidental Release

Spill Release Procedures:WIPE UP WITH SOLVENT AND RAGS.

## Handling

Handling and Storage Precautions:AVOID CONTACT W/SPARK OR OPEN FLAME.  
WASH HANDS AFTER USE. STORE IN CLOSED CONTAINER MATERIAL.

## Exposure Controls

Respiratory Protection:IN CONFINED AREAS USE ABSORPTIVE CANISTERS.

Ventilation:LOCAL EXHAUST RECOMMENDED

Protective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Other Protective Equipment:NONE

Work Hygienic Practices:WASH HANDS AFTER USE.

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:230F

Vapor Pres:30

Vapor Density:3

Spec Gravity:1.5

Solubility in Water:NIL

Appearance and Odor:WHITE, THIN PASTE, SULFIDE ODOR.

Percent Volatiles by Volume:10%

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:OPEN FLAME. STORE IN CLOSED CONTAINER

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.