

## **FUSE-ON 903 PRIMER FOR CPVC PLASTIC PIPE**

### **MSDS Number**

BBGCG

### **National Stock Number**

6810-00F000197

### **Product Name**

FUSE-ON 903 PRIMER FOR CPVC PLASTIC PIPE

### **Manufacturer**

R AND G SLOAN MANUFACTURING CO

### **Product Identification**

Product ID:FUSE-ON 903 PRIMER FOR CPVC PLASTIC PIPE

MSDS Date:01/01/1985

FSC:6810

NIIN:00F000197

MSDS Number: BBGCG

### **Responsible Party**

R & G SLOAN MANUFACTURING CO.

Emergency Phone: 213/875-0160

Cage: 18717

### **Contractor**

R & G SLOAN MANUFACTURING CO.

Cage: 18717

### **Ingredients**

TETRAHYDROFURAN (SARA III)

CAS: 109-99-9

RTECS: LU5950000

Fraction By Weight: >>90%

OSHA PEL200 PPM/250 STEL

ACGIH TLV: 200 PPM/250STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

DYE TRACE

Fraction By Weight: TRC

### **Hazards**

Effects of Overexposure:SEVERE OVER EXPOSURE MAY RESULT IN NAUSEA, DIZZINESS, HEADACHE. CAN CAUSE NARCOSIS.

### **First Aid**

First Aid:INHALATION:REMOVE TO FRESH AIR AND GIVE ARTIF. RESP. IF BREATHING STOPPED. SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES. SKIN: WASH WITH PLENTY OF WATER FOR 15 MINUTES. EYES:FLUSH WITH WATER FOR 15 MI NUTES. INGESTION: DO NOT INDUCE VOMITING.

### **Fire Fighting**

Flash Point:6F T.O.C.

Lower Limits:2  
Upper Limits:11  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICALS  
Fire Fighting Procedures:CLOSE OR CONFINED QUARTERS REQUIRE SELF CONT.  
BREATHING APP.  
Unusual Fire/Explosion Hazard:FIRE HAZARD BECAUSE OF LOW FLASH POINTS.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. AVOID  
BREATHING OF VAPORS. KEEP LIQUID OUT OF EYES. USH WITH LARGE VOLUME  
OF WATER. CONTAIN LIQUID WITH SAND OR EARTH. PREVE LIQUID FROM  
ENTERING SEWERS.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM ALL SOURCES OF  
IGNITION. AVOID PROLONGED BREATHING OF VAPOR. USE WITH ADEQUATE  
NTILATION. AVOID CONTACT WITH SKIN.  
Other Precautions:STORE BETWEEN 40F AND 110F. FOLLOW PRECAUTIONARY  
INFORMATION GIVEN ON CONTAINER LABEL. ALL HANDLING EQUIPMENT SHOULD  
BE ELECICALLY GROUNDED.

## Exposure Controls

Respiratory Protection:RESPIRATORS FOR ORGANIC VAPORS.  
Ventilation:LOCAL EXHAUST PREFERRABLE  
Protective Gloves:RUBBER/PVA  
Eye Protection:CHEMICAL SAFETY GOGGLES  
Other Protective Equipment:IMPERVIOUS APRON  
Supplemental Safety and Health  
7606 CLYBOURN, SUN VALLEY, CALIFORNIA 91352.

## Chemical Properties

Boiling Pt:B.P. Text:151F THF  
Vapor Pres:190  
Vapor Density:2.49  
Spec Gravity:0.888  
Evaporation Rate & Reference:8.0 BUAC=1  
Solubility in Water:INFINITE  
Appearance and Odor:GREEN, WATER-THIN LIQUID, ETHERAL ODOR.  
Percent Volatiles by Volume:100

## Stability

Stability Indicator/Materials to Avoid:YES  
CAUSTICS, AMMONIA, INORGANIC ACIDS, CHLORINATED COMPOUNDS  
Stability Condition to Avoid:KEEP AWAY FROM ALL SOURCES OF IGNITION.  
Conditions to Avoid Polymerization:SOURCES OF IGNITION, STRONG OXIDANTS  
& ISOCYANATES.

## Disposal

Waste Disposal Methods:INCINERATE. EXCESSIVE QUANTITIES SHOULD NOT BE  
PERMITTED TO ENTER DRAINS. CONSULT DISPOSAL EXPERT. FOLLOW LOCAL,  
STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.