

## **EA 306 BLACK COPON**

### **MSDS Number**

BBGDB

### **National Stock Number**

6850-00F000216

### **Product Name**

EA 306 BLACK COPON

### **Manufacturer**

RELIANCE UNIVERSAL INC

### **Product Identification**

Product ID:EA 306 BLACK COPON

MSDS Date:01/01/1985

FSC:6850

NIIN:00F000216

MSDS Number: BBGDB

### **Responsible Party**

RELIANCE UNIVERSAL, INC.

Emergency Phone: 213/694-1873

Cage: 3A701

### **Contractor**

RELIANCE UNIVERSAL INC.

Cage: 3A701

### **Ingredients**

2-ETHOXYETHANOL (EGEE) (SARA III)

CAS: 110-80-5

RTECS: KK8050000

Fraction By Weight: 27.9%

OSHA PELS,200 PPM

ACGIH TLV: S, 5 PPM; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 9.65%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 12.1%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## ALIPHATICS

Fraction By Weight: 20.5%

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 8.2%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Effects of Overexposure:IRRITATION OF NOSE, THROAT AND EYES. HEADACHE, NAUSEA, AND VOMITING.

## First Aid

First Aid:REMOVE TO FRESH AIR AND CALL A PHYSICIAN. FLUSH SKIN AND EYE CONTACT WITH WATER. IF SWALLOWED, INDUCE VOMITING AND CALL A PHYSICIAN.

## Fire Fighting

Flash Point:22F

Extinguishing Media:SMALL FIRES: CO2 OR DRY CHEMICAL;LARGE: ALCOHOL TYPE FOAM.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. FLUSH WITH LARGE VOLUMES OF WATER.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & FIRE. DO NOT LEAVE CONTAINER OPEN. USE WITH ADEQUATE VENTILATIONOID PROLONGED OR REPEATED CONTACT WITH SKIN.

Other Precautions:AVOID CONTACT WITH EYES. AVOID PROLONGED OR REPEATEDBREATHING OF VAPOR.

## Exposure Controls

Respiratory Protection:ALL-PURPOSE CANISTER MASK. CHEMICAL CARTRIDGE RESPIRATOR.

Ventilation:LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) ACCEPTED.

Protective Gloves:RUBBER

Eye Protection:FACE SHIELD

Other Protective Equipment:NONE

Supplemental Safety and Health

ALSO CONTAINS 7.7% XYLENE TLV-100PPM, 10% ISOPROPYL ALCOHOL TLV-400PPM, 4% BUTYL CELLOSOLVE TLV-50PPM. EPOXY 40% BY TOTAL .

## Chemical Properties

Vapor Density: >AIR

Evaporation Rate & Reference: Percent Volatiles by Volume: 60.9

## Stability

Stability Indicator/Materials to Avoid: YES

NONE

Hazardous Decomposition Products: THERMAL: CARBON MONOXIDE AND/OR CARBON DIOXIDE

## Disposal

Waste Disposal Methods: ATOMIZE INTO AN INCINERATOR.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.