

## **URAFILM GLOSS L.S. CLEAR**

### **MSDS Number**

BBGGM

### **National Stock Number**

8010-00F000264

### **Product Name**

URAFILM GLOSS L.S. CLEAR

### **Manufacturer**

CHEMICAL COMMODITIES AGENCY INC

### **Product Identification**

Product ID:URAFILM GLOSS L.S. CLEAR

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000264

MSDS Number: BBGGM

### **Responsible Party**

CHEMICAL COMMODITIES AGENCY, INC.

Emergency Phone: 714/864-2310

Cage: 60777

### **Contractor**

CHEMICAL COMMODITIES AGENCY, INC.

HIGHLAND, CA 92346-2640

US

909-864-2310

Cage: 60777

### **Ingredients**

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 74.7%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 25.3%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

### **Hazards**

Effects of Overexposure:VAPORS: MIGHT BE IRRITATING TO EYES, NOSE &

THROAT. REPEATED EXCESSIVE EXPOSURE: HEADACHES, NAUSEA

## First Aid

First Aid:VAPOR CONTACT: PROVIDE FRESH AIR AND REST. SKIN CONTACT: WASH WITH MILD SOAP AND WATER, USE EMOLLIENT CREAM OR LOTION. EYES: WASH WITH GENTLE STREAM OF WATER FOR 5 MINUTES. SEE A DOCTOR IMMEDIATELY.

## Fire Fighting

Flash Point:81F T.C.C.  
Extinguishing Media:WATER FOG, FOAM, CO2 AND/OR DRY CHEMICALS  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:CONCENTRATED VAPORS MAY BE EXPLOSIVE.

## Accidental Release

Spill Release Procedures:AVOID SPARKS OR OPEN FLAMES. PROVIDE ADEQUATE VENTILATION. WIPE SPILLAGE AND SAFELY SCARD ABSORBENT MATERIALS. LARGE SPILLS SHOULD BE DIKED AND PUMPED INTO STE TANK.

## Handling

Handling and Storage Precautions:HANDLE AS A FLAMMABLE LIQUID. DO NOT STORE NEAR OPEN FLAMES NOR COMBUSTION CHAMBERS.  
Other Precautions:AVOID SPARKS AND OPEN FLAMES. AVOID SKIN & EYE CONTACT. KEEP CONTAINERS CLOSED.

## Exposure Controls

Respiratory Protection:AIR RESPIRATORS OR AIR MASK SUITABLE FOR ORGANIC VAPORS  
Ventilation:LOCAL EXHAUST PREFERRED  
Protective Gloves:RECOMMENDED  
Eye Protection:SPLASH-PROOF GOGGLES  
Other Protective Equipment:IMPERVIOUS APRON. EYEWASH FACILITY.  
Supplemental Safety and Health  
27447 PACIFIC STREET/HIGHLAND, CA 92346.

## Chemical Properties

Boiling Pt:B.P. Text:NOT DETERM.  
Spec Gravity:0.94  
Evaporation Rate & Reference:NOT DETERMINED  
Solubility in Water:INSOLUBLE  
Appearance and Odor:CLEAR WITH BENZOL-LIKE ODOR  
Percent Volatiles by Volume:74.7

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:AVOID STRONG OXIDIZING AGENTS  
Hazardous Decomposition Products:CO, CO2, & ACRID FUMES ON BURNING

## Disposal

Waste Disposal Methods:LANDFILL: CONSULT WITH LOCAL, STATE AND/OR FEDERAL SOLID WASTE REGULATIONS FOR PROPER AND SAFE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.