

RESIN 1063-5

MSDS Number

BBGGS

National Stock Number

8030-00F000269

Product Name

RESIN 1063-5

Manufacturer

KOPPERS COMPANY INC

Product Identification

Product ID: RESIN 1063-5

MSDS Date: 01/01/1985

FSC: 8030

NIIN: 00F000269

MSDS Number: BBGGS

Responsible Party

KOPPERS COMPANY, INC.

Emergency Phone: 412/227-2000

Cage: EO463

Contractor

KOPPERS COMPANY, INC.

PITTSBURGH, PA 15219-1818

US

Cage: EO463

Ingredients

VEHICLE, UNSPECIFIED

Fraction By Weight: 60%

STYRENE, MONOMER (SARA III)

CAS: 100-42-5

RTECS: WL3675000

Fraction By Weight: 40%

OSHA PEL100 PPM

ACGIH TLV: S,50PPM/100STEL;9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure: DIZZINESS, INCOORDINATION, SLIGHT NAUSEA, LOSS OF APPETITE.

First Aid

First Aid: CALL PHYSICIAN; GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING, PREFERABLY BY MOUTH TO MOUTH. IF SWALLOWED, DO NOT INDUCE VOMITING-CALL PHYSICIAN. EYE CONTACT: FLUSH WITH WATER AND SEE A PHYSICIAN. WASH FROM SKIN WITH SOAP AND WATER.

Fire Fighting

Flash Point:85F
Lower Limits:1.1
Upper Limits:6.1
Extinguishing Media:FOAM, STEAM, WATER FOG, DRY CHEMICALS OR CO2
Fire Fighting Procedures:RUBBERIZED PROTECTIVE CLOTHING AND SELF CONT. BREATHING APP.
Unusual Fire/Explosion Hazard:VAPOR FORMS EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER LIMITS. WATER: TO COOL CONTAINERS.

Accidental Release

Spill Release Procedures:REMOVE OPEN FLAME, SPARKS, HOT SURFACES AND OXIDIZING AGENTS. CLEAN UP WITH ABSORBENDILUENT. AVOID BREATHING VAPORS. USE PROTECTIVE MEASURES OUTLINED IN SECON VIII BELOW.

Handling

Handling and Storage Precautions:STORE IN CLOSED, PROPERLY LABELED CONTAINER IN A COOL, VENTILATED AREA. KEEP AWAY FROM HEAT, ON FLAMES AND OXIDIZING AGENTS.
Other Precautions:DO NOT TRANSFER TO UNMARKED CONTAINER. IF O2 LEVEL IS < 19.5% AND/OR RESIN VAPOR CONC. IS 2% FOR CANISTERS USE AIR SUPPLIED ITS. USE WITH ADEQUATE VENTILATION. HARMFUL OR FATAL IF SWAL.

Exposure Controls

Respiratory Protection:NIOSH/MESA APPROVED RESPIRATORY PROTECTION WHERE REQUIRED.
Ventilation:LOCAL EXHAUST WHERE NECESSARY TO KEEP VAPORS < OSHA LIM.
Protective Gloves:RUBBER
Eye Protection:CHEMICAL SAFETY GOGGLES
Other Protective Equipment:IF NECESSARY, RUBBER APRON, SHOES OR BOOTS
Supplemental Safety and Health
KOPPERS BUILDING, PITTSBURGH, PENNSYLVANIA 15219.

Chemical Properties

Boiling Pt:B.P. Text:295F
Vapor Density:>AIR
Spec Gravity:1.15
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:VISCOUS LIQUID, STYRENE ODOR
Percent Volatiles by Volume: 45

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS
Stability Condition to Avoid:OPEN FLAME, HEAT, OXIDIZING AGENTS, FREE RAD.CATLST , PEROX.
Hazardous Decomposition Products:SMOKE, CARBON MONOXIDE, CARBON DIOXIDE
Conditions to Avoid Polymerization:OPEN FLAME, HEAT, OXIDIZING AGENTS, FREE RAD CATLS , PEROX.

Disposal

Waste Disposal Methods:USE EITHER APPROVED SANITARY LAND FILL OR INCINERATION. DO NOT INCINERATE CLOSED CONTAINERS. DISPOSAL MUST BE CARRIED OUT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

