



SEALFAS COATING (WATER BASED COATING)

MSDS Number

BBGGW

National Stock Number

8010-00F000272

Product Name

SEALFAS COATING (WATER BASED COATING)

Manufacturer

H B FULLER COMPANY

Product Identification

Product ID:SEALFAS COATING (WATER BASED COATING)

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000272

MSDS Number: BBGGW

Responsible Party

H.B. FULLER COMPANY

Emergency Phone: 612/645-3401

Cage: 9R359

Contractor

HB FULLER CO.

PALATINE, IL 60067

US

847-358-9500/612-236-5842

Cage: 5P957

Ingredients

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight:

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

VINYL ACETATE (SARA III)

CAS: 108-05-4

RTECS: AK0875000

Fraction By Weight:

OSHA PEL10 PPM/15 STEL

ACGIH TLV: 10 PPM/15,A3 STEL;93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:EYE CONTACT WILL CAUSE IRRITATION. PROLONGED



CONTACT MAY CAUSE IRRITATION TO SKIN.

First Aid

First Aid:EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER. CONSULT PHYSICIAN IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Fire Fighting

Extinguishing Media: DRY CHEMICAL, FOAM, CARBON DIOXIDE OR WATER SPRAY IF DRIED.

Fire Fighting Procedures: FULL PROTECTIVE EQUIPMENT, SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: CONTAIN AND REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions: DO NOT FREEZE, DO NOT STORE NEAR HEATED PIPES.

Other Precautions: NONE KNOWN.

Exposure Controls

Respiratory Protection: NOT REQUIRED UNDER NORMAL USE CONDITIONS.

Ventilation: STANDARD INDUSTRIAL VENTILATION

Protective Gloves: RECOMMENDED

Eye Protection: SAFETY GLASSES

Other Protective Equipment: EYE WASH.

Supplemental Safety and Health

2400 KASOTA AVENUE ST. PAUL, MINNESOTA 55108.

Chemical Properties

Boiling Pt: B.P. Text: >200F

Vapor Density: Evaporation Rate & Reference: < ETHER

Percent Volatiles by Volume: 40

Stability

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: FUMES MAY CONTAIN CARBON MONOXIDE

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.