

## **M&T INSTANT NICKEL CARBONATE**

### **MSDS Number**

BBGJC

### **National Stock Number**

6810-00F000307

### **Product Name**

M&T INSTANT NICKEL CARBONATE

### **Manufacturer**

ELF ATOCHEM NORTH AMERICA INC AGCHEM DIV

### **Product Identification**

Product ID:M&T INSTANT NICKEL CARBONATE

MSDS Date:07/01/1979

FSC:6810

NIIN:00F000307

MSDS Number: BBGJC

### **Responsible Party**

ELF ATOCHEM NORTH AMERICA INC AGCHEM DIV

2000 MARKET ST

PHILADELPHIA , PA 19103-3222

US

Emergency Phone: 409-779-0060/215-419-7667

Info Phone: 215-419-7667/409-779-0060

Cage: 86460

### **Contractor**

ELF ATOCHEM NORTH AMERICA INC

PHILADELPHIA, PA 19103-3222

US

800-245-5858

Cage: 86460

### **Ingredients**

NICKEL CARBONATE DIHYDRATE

CAS: 3333-67-3

Fraction By Weight: 100%

### **Hazards**

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, ALLERGIC SKIN REACTION.

### **First Aid**

First Aid:SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. EYES: IMMEDIATELY FLUSH W/PLENTY OF WATER FOR 15 MINS.

INGESTION: NEVER GIVE FLUIDS/INDUCE VOMITING IF UNCONSCIOUS/HAVING CONVULSIONS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

### **Fire Fighting**

Extinguishing Media:WATER SPRAY, CO2, FOAM, DRY CHEMICAL.  
Fire Fighting Procedures:AVOID EYE & SKIN CONTACT. DON'T BREATHE FUMES/DUST.  
Unusual Fire/Explosion Hazard:DUST MAY BE IRRITATING IF EXPOSED TO ELEVATED TEMPS/OPEN FLAMES.

## Accidental Release

Spill Release Procedures:MAY INJURE AQUATIC LIFE IF DISCHARGED TO OPEN WATERS. CONFINE AREA. CAREFULLY SWEEP UP PRODUCT & TRANSFER TO A SUITABLE CONTAINER FOR DISPOSAL/RECOVERY OF NICKEL.

## Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED. USE W/ADEQUATE VENTILATION. NORMAL WAREHOUSE STORAGE IN A COOL DRY AREA.

Other Precautions:AVOID BREATHING DUST. AVOID PROLONGED/REPEATED CONTACT W/SKIN.

## Exposure Controls

Respiratory Protection:WEAR AN APPROVED DUST RESPIRATOR SUITABLE FOR NICKEL DUSTS.

Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): REQUIRED.

Eye Protection:CHEMICAL WORKERS GOGGLES

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

## Chemical Properties

Solubility in Water:SLIGHT

Appearance and Odor:LIGHT GREEN POWDER W/CHARACTERISTIC ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES

## Disposal

Waste Disposal Methods:CHEMICALLY TREAT WASTE TO RECOVER NICKEL. DISPOSE OF AS SOLID WASTE IN APPROVED DUMPING AREA IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.