
FAULT FINDER PENETRANT GROUP 1 &1A

MSDS Number

BBGLK

National Stock Number

6850-00F000357

Product Name

FAULT FINDER PENETRANT GROUP 1 &1A

Manufacturer

CROWN INDUSTRIAL PRODUCTS COMPANY

Product Identification

Product ID:FAULT FINDER PENETRANT GROUP 1 &1A

MSDS Date:01/01/1985

FSC:6850

NIIN:00F000357

MSDS Number: BBGLK

Responsible Party

CROWN INDUSTRIAL PRODUCTS COMPANY

Emergency Phone: 815/648-2424

Cage: 93281

Contractor

CROWN INDUSTRIAL PRODUCTS COMPANY

Cage: 93281

Ingredients

SYNTHETIC LUBRICANT (CAS # 9003-1308)

CAS: 9003-13-8

RTECS: TR4680000

Fraction By Weight: >10%

AROMATIC HYDROCARBON

Fraction By Weight:

ACGIH TLV: 200PPM

ISOBUTANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 15%

ACGIH TLV: 1000PPM

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

Hazards

Effects of Overexposure:EXCESSIVE INHALATION MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, SEVERE EYE IRRITATION, DRYING OF SKIN.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. CALL PHYSICIAN. DO NOT INDUCE VOMITING. DO NOT ADMINISTER EPINEPHRINE OR SIMILAR DRUGS. EYE: FLUSH WITH WATER. SKIN: WASH WITH MILD SOAP. APPLY SKIN CREAM.

Fire Fighting

Lower Limits:1.8

Upper Limits:9.5

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:TREAT AS CLASS "B" FIRE.

Unusual Fire/Explosion Hazard:TREAT AS CYLINDER OF COMPRESSED GAS.

Accidental Release

Spill Release Procedures:VENTILATE AREA, CLEAN WITH CHLORINATED SOLVENT.

Handling

Handling and Storage Precautions:DO NOT STORE IN DIRECT SUNLIGHT, NEAR OPEN FLAME OR RADIATORS. DO NOT STORE AT TEMPERATURES INXCESS OF 120F. AVOID CONTACT WITH SKIN.

Other Precautions:USE ONLY AS DIRECTED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

Exposure Controls

Ventilation:LOCAL EXHAUST ADEQUATE

Eye Protection:SAFETY GLASSES, FACESHIEL

Supplemental Safety and Health

100 STATELINE ROAD, HEBRON, IL 60034.

Chemical Properties

Boiling Pt:B.P. Text:>300F

Vapor Density:>1

Spec Gravity:Evaporation Rate & Reference:Solubility in Water:NEGATIVE

Appearance and Odor:RED/ AROMATIC ODOR

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT SPRAY INTO OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE & OTHER TOXIC MATERIALS IN SMALL QUANTITIES

Disposal

Waste Disposal Methods:AEROSOL CONTAINER: DO NOT PUNCTURE OR INCINERATE CAN. DISPOSE OF CONTAINER IN A SAFE FASHION USING LAND FILL OR OTHER APPROPRIATE METHODS IN ACCORDANCE WITH FEDERAL, STATE OR LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.