

INMAC ANTI-STATIC SPRAY

MSDS Number

BBGLV

National Stock Number

6850-00F000367

Product Name

INMAC ANTI-STATIC SPRAY

Manufacturer

INMAC

Product Identification

Product ID:INMAC ANTI-STATIC SPRAY

MSDS Date:01/01/1985

FSC:6850

NIIN:00F000367

MSDS Number: BBGLV

Responsible Party

INMAC

Cage: 3T092

Contractor

INMAC

Cage: 3T092

Ingredients

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS: 71-55-6

RTECS: KJ2975000

Fraction By Weight: 50 - 70%

OSHA PEL350 PPM/450 STEL

ACGIH TLV: 350 PPM/450STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 50 - 75%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

CARBON DIOXIDE

CAS: 124-38-9

RTECS: FF6400000

Fraction By Weight: 5%

OSHA PEL5000 PPM

ACGIH TLV: 5000PPM/30000STEL;93

Hazards

Effects of Overexposure: EXCESSIVE INHALATION MAY CAUSE NASAL IRRITATION. EYES MAY BE PAINFUL FOR A TIME AFTER RINSING OUT.

First Aid

First Aid: IF UNCONSCIOUS, REMOVE VICTIM TO FRESH AIR AND CALL A PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER. IF UNCONSCIOUS FROM INHALATION DO NOT GIVE ADRENALINE-TYPE DRUGS. THIS EFFECT WOULD ONLY OCCUR IN CASES OF EXTREME INHALATION.

Fire Fighting

Extinguishing Media: WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL FOAM

Fire Fighting Procedures: USE SHIELDING TO PROTECT AGAINST BURSTING CONTAINERS.

Unusual Fire/Explosion Hazard: AT ELEVATED TEMPERATURES (>130F) CONTAINERS MAY VENT, RUPTURE, OR BURST.

Accidental Release

Spill Release Procedures: AVOID BREATHING VAPORS, AVOID SKIN CONTACT WITH LIQUID. REMOVE IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL AND DISPOSE OF AS WITH OIL- OR GASOLINE-SOAKED RAGS.

Handling

Handling and Storage Precautions: DO NOT STORE WHERE TEMPERATURES EXCEED 54°C, 130°F.

Other Precautions: PLEASE READ AND FOLLOW DIRECTIONS ON PRODUCT LABEL; THEY ARE YOUR BEST GUIDE TO USING THIS PRODUCT IN THE MOST EFFECTIVE WAY AND GIVE NECESSARY PRECAUTIONS TO PROTECT YOUR HEALTH.

Exposure Controls

Respiratory Protection: MASK MAY BE WORN FOR PROLONGED OR HEAVY SPRAYING

Ventilation: MECHANICAL (GENERAL AREA) SHOULD BE ON WHILE SPRAYING

Protective Gloves: RUBBER, POLYETH

Eye Protection: DO NOT SPRAY TOWARD EYES

Other Protective Equipment: DO NOT WEAR CLOTHING SOAKED BY SPRAY.

Supplemental Safety and Health

2465 AUGUSTINE DRIVE, P.O. BOX 4780, SANTA CLARA, CA

Chemical Properties

Boiling Pt: B.P. Text: N.A.

Vapor Density: >1

Spec Gravity: N.A.

Evaporation Rate & Reference: N.A.

Solubility in Water: 1-10%

Appearance and Odor: SOLID CONE WET MIST; CHLOR. SOLVENT ODOR

Percent Volatiles by Volume: 99

Stability

Stability Indicator/Materials to Avoid: YES

NONE WITH COMMON MATERIALS

Hazardous Decomposition Products: CARBON MONOXIDE, PHOSGENE, HYDROCHLORIC ACID.

Disposal

Waste Disposal Methods: DO NOT PUNCTURE OR INCINERATE CONTAINERS. GIVE EMPTY, LEAKING OR FULL CONTAINERS TO A DISPOSAL SERVICE EQUIPPED TO SAFELY HANDLE AND DISPOSE OF PRESSURIZED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.