

MASURY RUST NO MORE SPRAY ENAMEL

MSDS Number

BBGMD

National Stock Number

8010-00F000374

Product Name

MASURY RUST NO MORE SPRAY ENAMEL

Manufacturer

ILLINOIS BRONZE POWDER AND PAINT COMPANY

Product Identification

Product ID: MASURY RUST NO MORE SPRAY ENAMEL

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00F000374

MSDS Number: BBGMD

Responsible Party

ILLINOIS BRONZE POWDER AND PAINT COMPANY

Emergency Phone: 312/438-8201

Cage: 91794

Contractor

ILLINOIS BRONZE PAINT COMPANY

LAKE ZURICH, IL 60047-2580

US

800-228-5635

Cage: 91794

Ingredients

HEXANE (N-HEXANE)

CAS: 110-54-3

RTECS: MN9275000

Fraction By Weight: 0-12%

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 0-5%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 30%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 0-5%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-BUTOXYETHANOL

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight: 0-5%

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

Hazards

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE. GET FRESH AIR. EYES: FLUSH IMMEDIATELY WITH RUNNING WATER FOR 15 MINUTES. TAKE TO PHYSICIAN. SKIN: WIPE OFF WITH TOWEL, REMOVE REMAINING WITH TURPENTINE OR LACQUER THINNER IN CASE OF LACQUER. WASH WITH SOAP & WATER.

Fire Fighting

Flash Point:-40F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WEAR GOGGLES, SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CANS WILL RUPTURE FROM INTERNAL PRESSURE AT ABOUT 190F. AND DISCHARGE FLAMMABLE CONTENTS.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGOF NFPA CLASS 1A FLAMMABLE LIQUIDS.

Other Precautions:DO NOT SPRAY IN EYES. DO NOT PUNCTURE OR INCINERATE CANS. DO NOT STICK PIN, NAIL OR OTHER SHARP OBJECTS INTO OPENING ON TOP CAN. DO NOT FLAME CUT OR WELD DRY COATING W/OUT RESPIRATOR.

Exposure Controls

Respiratory Protection:NONE REQUIRED PROVIDED VENTILATION IS SUFFICIENT
Ventilation:GENERAL DILUTION OR LOCAL EXHAUST TO KEEP BELOW TLV'S
Protective Gloves:NONE
Eye Protection:NONE REQUIRED
Supplemental Safety and Health
300 E. MAIN STREET/ LAKE ZURICH, ILLINOIS 60047.

Chemical Properties

Boiling Pt:B.P. Text:42-391F
Vapor Density:>AIR
Evaporation Rate & Reference:>ETHER
Percent Volatiles by Volume:89

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:HYDROGEN CHLORIDE, CARBON MONOXIDE,
PHOSGENE

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.