

## **ARCHITECTURAL LATEX BLOCK FILLER - WHITE**

### **MSDS Number**

BBGMF

### **National Stock Number**

8010-00F000375

### **Product Name**

ARCHITECTURAL LATEX BLOCK FILLER - WHITE

### **Manufacturer**

MOBILE PAINT MFG CO INC

### **Product Identification**

Product ID:ARCHITECTURAL LATEX BLOCK FILLER - WHITE

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000375

MSDS Number: BBGMF

### **Responsible Party**

MOBILE PAINT MFG. CO., INC.

Emergency Phone: 205/653-0110

Cage: 88633

### **Contractor**

MOBILE PAINT MANUFACTURING CO INC

717

THEODORE, AL 36582

US

334-443-6110

Cage: 88633

### **Ingredients**

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1.8%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 0.3%

OSHA PEL100 PPM

### **Hazards**

Effects of Overexposure:INHALATION: MAY CAUSE HEADACHE, NAUSEA. SKIN:

PRIMARY IRRITATION. EYES: PRIMARY IRRITATION.

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: REMOVE WITH SOAP & WATER. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. INGESTION: DRINK 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT MD OR POISON CONTROL IMMEDIATELY

## Fire Fighting

Flash Point:DOES NOT FLASH

Lower Limits:0.8

Extinguishing Media:FOAM, ALCOHOL FOAM, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:RETURN MATERIAL TO CONTAINER.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. DO NOT FREEZE. STORE LARGE QUANTITIES ONLY IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precautions:DO NOT HANDLE UNTIL THE MANUFACTURER SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

## Exposure Controls

Respiratory Protection:CHEMICAL-MECHANICAL RESPIRATOR IN RESTRICTED VENTILATION

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:PROTECTIVE OUTERWEAR

Supplemental Safety and Health

P.O. BOX 717, THEODORE, AL 36590.

## Chemical Properties

Vapor Density:>AIR

Evaporation Rate & Reference:< ETHER

Percent Volatiles by Volume:61

## Stability

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:FIRE

Hazardous Decomposition Products:OXIDIZING MATERIALS WILL BE GIVEN OFF.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.