

SATIN LATEX HOUSE PAINT MASURY 7300-6

MSDS Number

BBGMM

National Stock Number

8010-00F000381

Product Name

SATIN LATEX HOUSE PAINT MASURY 7300-6

Manufacturer

VALSPAR CORP

Product Identification

Product ID: SATIN LATEX HOUSE PAINT MASURY 7300-6

MSDS Date: 02/07/1986

FSC: 8010

NIIN: 00F000381

MSDS Number: BBGMM

Responsible Party

VALSPAR CORPORATION

1101 THIRD STREET SOUTH

MINNEAPOLIS , MN 55415

Emergency Phone: (612) 332-7371

Info Phone: (612) 332-7371

Cage: 06758

Contractor

VALSPAR CORPORATION

MINNEAPOLIS, MN 55415

US

612-332-7371/888-345-5732

Cage: 23526

Ingredients

MICA - SILICATES (< 1% CRYSTALLINE SILICA)

CAS: 12001-26-2

RTECS: VV8760000

OSHA PEL20 MPPCF

ACGIH TLV: 3 MG/M3 RDUST; 9293

SILICA, AMORPHOUS, PRECIPITATED AND GEL

CAS: 7699-41-4

RTECS: VV8850000

OSHA PEL20 MPPCF

ACGIH TLV: 10 MG/M3 TDUST; 9293

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION. INHALATION: NAUSEA.
SKIN: DRYING.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN: DRYING. EYES: IRRITATION. INHALATION:
NAUSEA.

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE AREA. EYES: FLUSH W/WATER
FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER.

Fire Fighting

Flash Point Method:TCC
Flash Point:>141F
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, & WATER FOG
Fire Fighting Procedures:FIREFIGHTERS MUST WEAR SELF-CONTAINED
BREATHING APPARATUS/AIR MASKS. CONTAINERS EXPOSED TO FIRE SHOULD BE
KEPT COOL W/WATER SPRAY.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SPILLS W/INERT
ABSORBENT.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DON'T STORE >120F. KEEP FROM FREEZING. EMPTY CONTAINERS MAY
CONTAIN PRODUCT RESIDUE.
Other Precautions:DON'T CUT, PUNCTURE OR WELD CONTAINERS. ALL LABEL
WARNINGS MUST BE OBSERVED UNTIL CONTAINER HAS BEEN CLEANED.
RECONDITIONED OR PROPERLY DISPOSED OF.

Exposure Controls

Respiratory Protection:WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR
NIOSH/MSHA APPROVED DURING & AFTER APPLICATION UNLESS AIR
MONITORING VAPOR/MIST LEVELS ARE Ventilation:REQUIRED WHEN SPRAYING OR APPLYING IN CONFINED AREA.
Protective Gloves:USUAL HAND PROTECTION
Eye Protection:USUAL EYE PROTECTION
Other Protective Equipment:USUAL CLOTHING FOR PAINTING OPERATIONS.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F
Vapor Pres:24.0
Vapor Density:0.63
Spec Gravity:1.38

Evaporation Rate & Reference:(BU AC = 1): 0.36
Solubility in Water:YES
Appearance and Odor:NORMAL FOR A COATINGS PRODUCT.
Percent Volatiles by Volume:62.40%

Stability

Stability Indicator/Materials to Avoid:YES
AVOID WATER-REACTIVE MATERIALS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:SILICON DIOXIDE, METAL OXIDES,
HALIDES, CO₂, MONOXIDE.

Disposal

Waste Disposal Methods:DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER
THAT COMPLIES W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.