

PERFECTION SEMI-GLOSS ENAMELS, 1200 LINE

MSDS Number

BBGMV

National Stock Number

8010-00F000388

Product Name

PERFECTION SEMI-GLOSS ENAMELS, 1200 LINE

Manufacturer

CONCHEMCO INCORPORATED

Product Identification

Product ID:PERFECTION SEMI-GLOSS ENAMELS, 1200 LINE

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000388

MSDS Number: BBGMV

Responsible Party

CONCHEMCO, INCORPORATED

Emergency Phone: 301/252-1988

Cage: CONCH

Contractor

CONCHEMCO, INCORPORATED

Cage: CONCH

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 30%

OSHA PEL100 PPM

Hazards

Effects of Overexposure:EXCESSIVE INHALATION WILL IRRITATE NOSE THROAT.
MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, VOMITING.

First Aid

First Aid:EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CALL
PHYSICIAN. SKIN: REMOVE WITH SOAP & WATER. REMOVE CONTAMINATED
CLOTHING. FUMES: REMOVE TO FRESH AIR, RESTORE BREATHING. CALL
PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

Fire Fighting

Flash Point:102F SETAFLASH

Extinguishing Media:FOAM, CO2, OR CHEMICAL

Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS

Unusual Fire/Explosion Hazard:DO NOT APPLY TO HOT SURFACES. CLOSED

CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
PROLONGED BREATHING OF VAPORS. VENTILATE AREA.EMOVE WITH INERT
ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLE LIQUIDS.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:CHEMICAL MECHANICAL FILTER TYPE, OR AIR LINE TYPE IF CONFINED
Ventilation:GENERAL DILUTION, LOCAL EXHAUST
Protective Gloves:REQUIRED
Eye Protection:SPLASH PROOF EYEWEAR
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.
Supplemental Safety and Health
1401 SEVERN STREET/ BALTIMORE, MARYLAND 21230.

Chemical Properties

Boiling Pt:B.P. Text:360-400F
Vapor Density:> 1
Evaporation Rate & Reference:< ETHER
Percent Volatiles by Volume: 50

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products:THERMAL DECOMPOSITION: FUMES MAY CONTAIN CARBON MONOXIDE.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.