
DOOR-EASE STAINLESS STICK LUBRICANT

MSDS Number

BBGMY

National Stock Number

9160-00F000391

Product Name

DOOR-EASE STAINLESS STICK LUBRICANT

Manufacturer

AMERICAN GREASE STICK COMPANY

Product Identification

Product ID:DOOR-EASE STAINLESS STICK LUBRICANT

MSDS Date:08/01/1988

FSC:9160

NIIN:00F000391

MSDS Number: BBGMY

Responsible Party

AMERICAN GREASE STICK COMPANY

2651 HOYT STREET

MUSKEGON HTS. , MI 49444

Emergency Phone: (800) 253-0403

Info Phone: (800) 253-0403

Preparer: TOMMY JONES

Cage: EO473

Contractor

AMERICAN GREASE STICK COMPANY

729

MUSKEGON HTS., MI 49444

US

(800) 253-0403

Cage: EO473

Ingredients

PARAFFIN WAX

CAS: 8002-74-2

RTECS: RV0350000

Fraction By Weight: 30-45%

OSHA PEL2 MG/M3 (FUME)

ACGIH TLV: 2 MG/M3 (FUME); 9192

PETROLEUM OIL, ALAPHATIC

CAS: 68815-10-1

Fraction By Weight: 30-45%

NAPHTHENIC ACID, ZINC SALT

CAS: 12001-85-3

RTECS: OK9275000

Fraction By Weight: 1-5%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE SEVERE BURNS. INHALATION: ASPIRATION OF FUMES OR MIST MAY CAUSE RESPIRATORY PROBLEMS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES: IRRITATION. SKIN: MAY CAUSE SEVERE BURNS. INHALATION: ASPIRATION OF FUMES OR MIST MAY CAUSE RESPIRATORY PROBLEMS.

First Aid

First Aid:EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN. SKIN: WASH W/SOAP & WATER. GET MED ATTN. INGESTION: DON'T INDUCE VOMITING. CONSULT PHYSICIAN. INHALATION; REMOVE TO FRESH AIR. ADMINISTER ARTIFICIAL RESPIRATION AS NEEDED.

Fire Fighting

Flash Point Method:COC
Flash Point:380F
Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER FOG
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. USE WATER FOG TO MINIMIZE VAPORS IN AIR.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:DIKE AREA TO CONTAIN PRODUCT SPILL. ALLOW TO COOL, SCRAPE MATERIAL UP & PLACE IN CONTAINER FOR DISPOSAL.

Handling

Handling and Storage Precautions:STORE BELOW 120F. AVOID EXCESS HEAT & IGNITION SOURCES. STORE IN COOL AREAS.

Exposure Controls

Respiratory Protection:WEAR NIOSH-APPROVED RESPIRATOR FOR FUMES WHEN >TLV.
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION WHEN USING PRODUCT IN MOLTEN STATE.
Protective Gloves:RESISTANT
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS
Supplemental Safety and Health
PETROLEUM OIL IS SEVERELY HYDROTREATED OR SOLVENT REFINED. IT DOES NOT REQUIRE LABELING AS A CARCINOGEN.

Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:163F
Vapor Pres:NEGLIGIBLE
Spec Gravity:0.75
Solubility in Water:INSOLUBLE
Appearance and Odor:TAN WAXY SOLID W/BLAND PETROLEUM ODOR.
Percent Volatiles by Volume:NIL

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT & IGNITION SOURCES
Hazardous Decomposition Products:CO, CO2, ZINC

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND

FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.