
LATEX FLOOR ENAMEL 631-XX

MSDS Number

BBGPW

National Stock Number

8010-00F000431

Product Name

LATEX FLOOR ENAMEL 631-XX

Manufacturer

THE O'BRIEN CORP

Product Identification

Product ID:LATEX FLOOR ENAMEL 631-XX

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000431

MSDS Number: BBGPW

Responsible Party

THE O'BRIEN CORPORATION

Emergency Phone: 415/ 761-2300

Cage: EO477

Contractor

THE O'BRIEN CORPORATION

SOUTH SAN FRANCISCO, CA 94080

US

800-338-8084/415-761-2300

Cage: EO477

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ALCOHOL

Fraction By Weight:

ALIPHATIC HYDROCARBONS

Fraction By Weight:

ACGIH TLV: 500PPM

AMMONIUM HYDROXIDE (SARA III)

CAS: 1336-21-6

RTECS: BQ9625000

Fraction By Weight:

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

MERCURY (SARA III)

CAS: 7439-97-6

RTECS: OV4550000

Fraction By Weight: TRC.

OSHA PELS, C, 0.1 MG/M3

ACGIH TLV: S, 0.05 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure:INHALATION: MAY CAUSE HEADACHE & NAUSEA.
PRIMARY IRRITATION TO SKIN & EYES.

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SKIN: REMOVE WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.

Fire Fighting

Flash Point:NONE

Fire Fighting Procedures:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING. KEEP OUT OF THE REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:PARTICLE MASK FOR SPRAYING.

Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL EXHAUST ACCEPTABLE

Eye Protection:GLASSES OR GOGGLES

Supplemental Safety and Health

WESTERN REGION/ 450 EAST GRAND AVENUE/ SOUTH SAN FRANCISCO, CA 94080.

Chemical Properties

Boiling Pt:B.P. Text:212F

Vapor Density:>AIR

Evaporation Rate & Reference:Percent Volatiles by Volume: 67

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:NON-PHOTOCHEMICALLY REACTIVE

Disposal

Waste Disposal Methods:DISPERSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.