https://msdsreport.com/msds/BBGPZ

YELLOW TRAFFIC PAINT #382-15

MSDS Number

BBGPZ

National Stock Number

8010-00F000434

Product Name

YELLOW TRAFFIC PAINT #382-15

Manufacturer

O'BRIEN CORP

Product Identification

Product ID:YELLOW TRAFFIC PAINT #382-15 MSDS Date:01/01/1985 FSC:8010 NIIN:00F000434 MSDS Number: BBGPZ

Responsible Party

O'BRIEN CORPORATION

Emergency Phone: 415/ 761-2300

Cage: 91988

Contractor

O'BRIEN CORPORATION

SOUTH SAN FRANCISCO, CA 94080

(800) 338-8084

Cage: 91988

Ingredients

ALIPHATIC HYDROCARBONS Fraction By Weight: 57% ACGIH TLV: 300PPM

SOLVENTS (ESTER SOLVENTS, TYPE NOT SPECIFIED) Fraction By Weight: ACGIH TLV: 150PPM

LEAD (SARA III) CAS: 7439-92-1 RTECS: OF7525000 Fraction By Weight: 14.6% OSHA PEL0.05 MG/M3;1910.1025 ACGIH TLV: 0.15 MG/M3;DUST 9192 EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

Hazards



Effects of Overexposure: INHALATION: ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid:INGESTION: CONTACT PHYSICIAN IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR-RESTORE BREATHING, USE OXYGEN IF NECESSARY. EYES: CONTACT PHYSICIAN. FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SKIN: WIPE OFF WITH A RAG AND WASH THOROUGHLY W/SOAP & WATER

•

Fire Fighting

Flash Point:20F Lower Limits:0.9 Extinguishing Media:CO2, FOAM OR DRY CHEMICAL Fire Fighting Procedures:DO NOT USE WATER ON BURNING LIQUIDS. Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

Accidental Release

Spill Release Procedures:EXTINGUISH SOURCES OF IGNITION. VENTILATE TO PREVENT BUILD UP OF VAPORS. SOAK UP WITSAWDUST OR SIMILAR INERT MATERIAL.

Handling

Handling and Storage Precautions: STORE UPRIGHT IN SEALED CONTAINERS AWAY FROM HEAT OF FLAME. KEEP CONTAINER TIGHTLY SEALED WHENOT IN USE.

Other Precautions:DO NOT POUR INTO UNMARKED CONTAINER. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:AIR SUPPLIED RESPIRATOR IN CONFINED PLACES Ventilation:LOCAL EXHAUST OR OPEN AIR Protective Gloves:IF NEEDED Eye Protection:SAFETY GLASSES Supplemental Safety and Health 450 EAST GRAND AVENUE, SOUTH SAN FRANCISCO, CA 94080.

Chemical Properties

Boiling Pt:B.P. Text:198-267F Vapor Density:>AIR Evaporation Rate & Reference:< ETHER Percent Volatiles by Volume:60

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:HEAT, SPARKS AND FLAME

Disposal

Waste Disposal Methods:DISCARD IN SEALED METAL CONTAINER AWAY FROM HEAT AND FLAME IN ACCORDANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.