
VERSAFLEX HEAVY DUTY GLOSS ENAMEL, 612-05

MSDS Number

BBGQC

National Stock Number

8010-00F000436

Product Name

VERSAFLEX HEAVY DUTY GLOSS ENAMEL, 612-05

Manufacturer

O'BRIEN CORP

Product Identification

Product ID:VERSAFLEX HEAVY DUTY GLOSS ENAMEL, 612-05

MSDS Date:05/31/1986

FSC:8010

NIIN:00F000436

MSDS Number: BBGQC

Responsible Party

O'BRIEN CORPORATION

430 EAST GRAND AVENUE

SOUTH SAN FRANCISCO , CA 94080

Emergency Phone: (415) 761-2300

Info Phone: (415) 761-2300

Cage: 91988

Contractor

O'BRIEN CORPORATION

SOUTH SAN FRANCISCO, CA 94080

(800) 338-8084

Cage: 91988

Ingredients

ALIPHATIC HYDROCARBONS

Fraction By Weight: 50%

ACGIH TLV: 100PPM

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES

CAS: 64742-88-7

Fraction By Weight: 5%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

ALUMINUM (SARA III)

CAS: 7429-90-5

RTECS: BD0330000

Fraction By Weight: 15%

OSHA PEL15MG/M3 DUST/5 FUME

ACGIH TLV: 10MG/M3 DUST; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION TO MOUTH/THROAT/GASTROINTESTINAL & RESPIRATORY TRACT, W/CNS DEPRESSION, HEADACHE, DIZZINESS, NAUEA, ABDOMINAL PAIN, DIARRHEA, LOSS OF CONSCIOUSNESS, COMA, ANESTHETIC/STAGGERING GAIT. EYE: IRRITATION & BLURRED VISION. SKIN: IRRITATION & DERMATITIS. INGESTION: VOMITING.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INGESTION: ASPIRATION OF THIS MATERIAL INTO THE LUNGS DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS/FATAL.
INHALATION: PROLONGED/REPEATED OVEREXPOSURE TO SOLVENTS CAUSES PERMANENT BRAIN/CENTRAL NERVOUS SYSTEM DAMAGE.

First Aid

First Aid:INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. KEEP PERSON WARM/QUIET. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. EYE: FLUSH W/COOL WATER FOR 15 MINUTES. SKIN: WIPE OFF W/A RAG & WASH THOROUGHLY W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:65F
Lower Limits:1.0%
Extinguishing Media:CO2, FOAM, DRY CHEMICAL OR WATER FOG
Fire Fighting Procedures:USE FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP/POSSIBLE AUTO-IGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT. DON'T HOT SURFACES.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. SOAK UP & REMOVE W/INERT ABSORBENT MATERIAL W/NON-SPARKING TOOLS. PROVIDE ADEQUATE VENTILATION.

Handling

Handling and Storage Precautions:STORE UPRIGHT IN SEALED CONTAINERS & USE AWAY FROM HIGH TEMPERATURE, SPARKS & FLAME. AVOID CONTACT W/SKIN. DON'T INGEST. FLAMMABLE LIQUIDS.
Other Precautions:KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. FOR BAKING FINISHES, VENT VAPORS EMITTED ON HEATING. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING/INHALING THE CONTENTS MAY BE HARMFUL/FATAL.

Exposure Controls

Respiratory Protection:USE A NIOSH/MSHA APPROVED PROPERLY FITTED MECHANICAL RESPIRATOR OR MASK TO AVOID BREATHING VAPOR OR SPRAY MIST DURING MIXING, SPRAYING, APPLICATION OR CURING.
Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION IN VOLUME/PATTERN TO KEEP
Protective Gloves:SYNTHETIC RUBBER
Eye Protection:GOGGLES, SAFETY GLASSES W/SIDESHIELDS
Other Protective Equipment:PROTECTIVE OVERALLS RECOMMENDED.
Work Hygienic Practices:REMOVE/WASH CONTAMINATED CLOTHING BEFORE RE-USE. DISCARD CONTAMINATED SHOES.
Supplemental Safety and Health
WT/GAL: 7.54 LBS. CHRONIC EXPOSURE TO SOLVENTS HAS BEEN SHOWN TO CAUSE DAMAGE TO KIDNEYS, LIVER, LUNGS BLOOD CELLS, BLOOD PRODUCING ORGANS (MARROW), BLOOD STORING ORGAN (SPLEEN), & PERIPHERAL NERVOUS SYSTEM.

Chemical Properties

Boiling Pt:B.P. Text:245-398F

Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:67.5%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, ACIDS, BASES
Stability Condition to Avoid:HEAT, HOT SURFACES, SPARKS, FLAME,
ELECTRICAL EQUIPMENT, & HIGH TEMPERATURE.
Hazardous Decomposition Products:CO, CO2, & NO2

Disposal

Waste Disposal Methods:DISPOSE IN SEALED METAL CONTAINER AWAY FROM HEAT
AND FLAME IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.
DON'T INCINERATE CLOSED CONTAINERS. FLAMMABLE LIQUID; UN1263.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.