

CHROME ALUMINUM ALKYD GLOSS ENAMEL, 612-05

MSDS Number

BBGQD

National Stock Number

8010-00F000437

Product Name

CHROME ALUMINUM ALKYD GLOSS ENAMEL, 612-05

Manufacturer

O'BRIEN CORP

Product Identification

Product ID:CHROME ALUMINUM ALKYD GLOSS ENAMEL, 612-05

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000437

MSDS Number: BBGQD

Responsible Party

O'BRIEN CORPORATION

Emergency Phone: 415/ 761-2300

Cage: 91988

Contractor

O'BRIEN CORPORATION

SOUTH SAN FRANCISCO, CA 94080

(800) 338-8084

Cage: 91988

Ingredients

ALIPHATIC HYDROCARBONS

Fraction By Weight: 57%

ACGIH TLV: 200PPM

Hazards

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR-RESTORE BREATHING, USE OXYGEN IF NECESSARY. INGESTION: CONTACT PHYSICIAN IMMEDIATELY. EYES: CONTACT A PHYSICIAN. FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SKIN: WIPE OFF WITH RAG & WASH WITH SOAP & WATER.

Fire Fighting

Flash Point:65F

Lower Limits:0.9

Extinguishing Media:CO2, FOAM OR DRY CHEMICAL

Fire Fighting Procedures:DO NOT USE WATER STREAM ON BURNING LIQUIDS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

Accidental Release

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION. VENTILATE TO PREVENT BUILD UP OF VAPORS. SOAK UP WITH SAWDUST OR SIMILAR INERT MATERIAL.

Handling

Handling and Storage Precautions:STORE UPRIGHT IN SEALED CONTAINERS
AWAY FROM HEAT OR FLAME.
Other Precautions:KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE. DO NOT
POUR INTO UNMARKED CONTAINER. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:USE RESPIRATOR OR MASK TO AVOID BREATHING OF
VAPOR OR SPRAY MIST.
Ventilation:LOCAL EXHAUST OR OPEN AIR TO KEEP BELOW TLV & LEL.
Protective Gloves:IF NEEDED
Eye Protection:SAFETY GLASSES
Supplemental Safety and Health
450 EAST GRAND AVENUE/ SOUTH SAN FRANCISCO, CA 94080.

Chemical Properties

Boiling Pt:B.P. Text:244-308F
Vapor Density:>AIR
Evaporation Rate & Reference:< ETHER
Percent Volatiles by Volume:58

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, SPARKS, FLAME

Disposal

Waste Disposal Methods:DISCARD IN SEALED METAL CONTAINER AWAY FROM HEAT
AND FLAME IN ACCORDANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.