



SYNTHETIC GLOSS ENAMEL, MED. GREEN 59-144

MSDS Number

BBGQG

National Stock Number

8010-00F000439

Product Name

SYNTHETIC GLOSS ENAMEL, MED. GREEN 59-144

Manufacturer

NAZ DAR COMPANY

Product Identification

Product ID:SYNTHETIC GLOSS ENAMEL, MED. GREEN 59-144

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000439

MSDS Number: BBGQG

Responsible Party

NAZ-DAR COMPANY

Emergency Phone: 312/ 943-8338

Cage: EO327

Contractor

NAZDAR COMPANY

CHICAGO, IL 60622-4292

US

312-943-8338;800-736-7636

Cage: 76708

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 25%

OSHA PEL100 PPM

LEAD NAPHTHANATE

CAS: 61790-14-5

RTECS: QK9150000

Fraction By Weight: 0.6%

ACGIH TLV: 0.2 MG/M3

LEAD (SARA III)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 10%

OSHA PEL0.05 MG/M3;1910.1025



ACGIH TLV: 0.15 MG/M3;DUST 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

CHROMIUM (SARA III)

CAS: 7440-47-3

RTECS: GB4200000

Fraction By Weight: 2%

OSHA PEL1 MG/M3

ACGIH TLV: 0.5 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. NOTIFY A PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH COPIOUS QUANTITIES OF RUNNING WATER FOR 15 MINUTES. TAKE TO PHYSICIAN FOR DEFINITIVE MEDICAL TREATMENT. SKIN: WASH W/SOAP& WATER.

Fire Fighting

Flash Point:140F T.C.C.

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM

Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASII FLAMMABLE LIQUIDS.

Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO T FLAME CUT, BRAZE OR WELD APPROVED OR APPROPRIATE VENTILATION

Exposure Controls

Respiratory Protection:MECHANICAL OR MECHANICAL CHEMICAL FILTER TYPE

Ventilation:GENERAL DILUTION, LOCAL EXHAUST

Protective Gloves:REQUIRED

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Supplemental Safety and Health

1087 N. NORTH BRANCH STREET/ CHICAGO, IL 60622.

Chemical Properties

Boiling Pt:B.P. Text:302F-399F

Vapor Density:>AIR

Evaporation Rate & Reference:< ETHER

Percent Volatiles by Volume:44

Stability



Stability Indicator/Materials to Avoid: YES

NA

Stability Condition to Avoid: NA

Hazardous Decomposition Products: CARBON MONOXIDE, OXIDES OF NITROGEN

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.