

## **MOLUB-ALLOY 936**

### **MSDS Number**

BBGRS

### **National Stock Number**

9150-00F000469

### **Product Name**

MOLUB-ALLOY 936

### **Manufacturer**

IMPERIAL OIL AND GREASE CO

### **Product Identification**

Product ID:MOLUB-ALLOY 936

MSDS Date:01/01/1985

FSC:9150

NIIN:00F000469

MSDS Number: BBGRS

### **Responsible Party**

IMPERIAL OIL & GREASE CO.

Emergency Phone: 213/ 478-3577

Cage: 4U543

### **Contractor**

IMPERIAL OIL & GREASE CO

HAWTHORNE, CA 90250

US

213-679-0271

Cage: 4U543

### **Ingredients**

TRICHLOROETHYLENE (SARA III)

CAS: 79-01-6

RTECS: KX4550000

OSHA PEL100 PPM/100 STEL

ACGIH TLV: 50 PPM/100,A5STEL;93

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

PETROLEUM LUBRICATING OIL

ACGIH TLV: 5 MG/M3

LEAD (SARA III)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 1.5%

OSHA PEL0.05 MG/M3;1910.1025

ACGIH TLV: 0.15 MG/M3;DUST 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

## Hazards

Effects of Overexposure:NO DATA.

## First Aid

First Aid:RINSE MATERIAL FROM EYES WITH WARM WATER; TREAT EYES WITH PROPRIETARY EYE WASH SOLUTION. TOXIC POTENTIAL IF INGESTED, DO NOT INDUCE VOMITING.

## Fire Fighting

Flash Point:500F, FLUID COMP

Extinguishing Media:FOAM, CO2

Fire Fighting Procedures:SAME AS FOR PETROLEUM

Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:CLEAN UP PROMPTLY BY MECHANICAL MEANS AND PROPRIETARY OIL-DRYING COMPOUND.

## Handling

Handling and Storage Precautions:FOLLOW SAME PROCEDURE AS FOR PETROLEUM BASE LUBRICATING GREASES. DO NOT STORE AT TEMPERATURES OVE 120F.

Other Precautions:THE NON-FLAMMABLE VOLATILE SOLVENT COMPONENT USED FOR EASE OF APPLICATION WILL EVAPORATE WITHIN A FEW HOURS FOLLOWING APPLICION AND IS NOT A SUSTAINING FEATURE OF THE PRODUCT.

## Exposure Controls

Ventilation:LOCAL EXHAUST, HIGH TEMPERATURE SERVICE ONLY

Protective Gloves:YES

Eye Protection:NOT REQUIRED

Other Protective Equipment:NONE FOR NORMALLY RECOMMENDED APPLICATIONS.

Supplemental Safety and Health

10906 WILSHIRE BLVD., LOS ANGELES, CA 90024

## Chemical Properties

Boiling Pt:B.P. Text:600F

Spec Gravity:1.13

Solubility in Water:SLIGHT

Appearance and Odor:DARK, PLASTIC SOLID, CHLORINATED SOLVENT ODOR.

Percent Volatiles by Volume:TRC.

## Stability

Stability Indicator/Materials to Avoid:NO

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXPOSURE TO METALLIC RED HEAT & OPEN FLAME.

Conditions to Avoid Polymerization:STORAGE AT TEMP ABOVE 120F.

## Disposal

Waste Disposal Methods:SOLID CHEMICAL WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.