

## **SUPER KOROPON 519 X 303**

### **MSDS Number**

BBGSM

### **National Stock Number**

8040-00F000486

### **Product Name**

SUPER KOROPON 519 X 303

### **Manufacturer**

DESOTO INC

### **Product Identification**

Product ID: SUPER KOROPON 519 X 303

MSDS Date: 01/01/1985

FSC: 8040

NIIN: 00F000486

MSDS Number: BBGSM

### **Responsible Party**

DESOTO, INC.

Emergency Phone: 312/ 391-9000

Cage: 32758

### **Contractor**

DESOTO, INC.

Cage: 32758

### **Ingredients**

STRONTIUM CHROMATE (SARA III)

CAS: 7789-06-2

RTECS: GB3240000

Fraction By Weight: 10%

OSHA PEL 0.1 PPM CRO3; CEILING

ACGIH TLV: 0.0005 MG CR/M3; A2; 93

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 20%

OSHA PEL 150 PPM

ACGIH TLV: 150 PPM/200 STEL; 9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

AROMATIC SOLVENT

Fraction By Weight:

ACGIH TLV: 100PPM

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 20%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

## First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. NOTIFY PHYSICIAN. SKIN: WASH AFFECTED AREAS WITH WATER. CONSULT PHYSICIAN. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN. INGESTION: CON SULT PHYSICIAN.

## Fire Fighting

Flash Point:33F, CLOSED CUP

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:WATER MAY BE USED TO COOL FIRE EXPOSED CONTAINERS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120 DEG.F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF FLAMBLE LIQUIDS.

Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO T SAND, FLAME CUT OR WELD W/OUT APPROVED RESPIRATOR.

## Exposure Controls

Respiratory Protection:NIOSH APPROVED MECHANICAL FILTER RESPIRATOR

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves:REQUIRED

Eye Protection:SPLASH PROOF EYEWEAR  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH  
CONTAMINATED CLOTHING  
Supplemental Safety and Health  
1700 S. MT. PROSPECT ROAD/ DES PLAINES, ILL. 60018 PRODUCT ALSO  
CONTAINS ALUMINUM PIGMENT

## **Chemical Properties**

Boiling Pt:B.P. Text:176-315F  
Vapor Density:Evaporation Rate & Reference:< ETHER  
Percent Volatiles by Volume:66

## **Stability**

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS.

## **Disposal**

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.