

FLAT BLACK 37038

MSDS Number

BBGSY

National Stock Number

8010-00F000493

Product Name

FLAT BLACK 37038

Manufacturer

U S PAINT LACQUER AND CHEMICAL CO

Product Identification

Product ID:FLAT BLACK 37038

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000493

MSDS Number: BBGSY

Responsible Party

U.S. PAINT LACQUER & CHEMICAL CO.

Emergency Phone: 314/ 621-0525

Cage: USPAI

Contractor

U.S. PAINT LACQUER & CHEMICAL/ST. LOUIS

Cage: USPAI

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 11.3%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 17.1%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 18.4%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 13.1%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 31.8%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:EYE & UPPER RESPIRATORY IRRITANT.

First Aid

First Aid:IF EXPOSED TO EXCESS VAPOR, REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION. IF SPLASHED ON SKIN OR IN EYES, FLUSH WITH LARGE AMOUNTS OF WATER AND SEEK IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point:32F, T.C.C.

Lower Limits:1.4

Extinguishing Media:DRY CHEMICAL OR FOAM

Unusual Fire/Explosion Hazard:DO NOT EXPOSE TO SPARK OR OPEN FLAME

Accidental Release

Spill Release Procedures:AFFECTED AREA SHOULD BE TREATED WITH AN ABSORBING COMPOUND AND THEN MATERIAL PLACED A TIGHTLY CLOSED CONTAINER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM SPARKS, HEAT, AND FLAMES.

Exposure Controls

Respiratory Protection:BUREAU OF MINES APPROVED MASK FOR REMOVAL OF PARTICULATE MATTER

Ventilation:SUFFICIENT TO KEEP AIR SUPPLY ABOVE TLV

Protective Gloves:RUBBER/PLASTIC

Eye Protection:GOGGLES

Other Protective Equipment:HYPERSENSITIVE PERSONS SHOULD USE PROTECTIVE

CREAM
Supplemental Safety and Health
2101 SINGLETON ST. ST. LOUIS, MO 63103. PRODUCT ALSO CONTAINS ISOBUTYL
ALCOHOL 8.(NP9625000).

Chemical Properties

Boiling Pt:B.P. Text:172-288F
Vapor Density:>AIR
Evaporation Rate & Reference:< ETHER
Percent Volatiles by Volume:71.4

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:EXCESS HEAT AND/OR OXIDIZING MATERIALS

Disposal

Waste Disposal Methods:IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL
ENVIRONMENTAL CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.