

FUSE-ON 940 SOLVENT CEMENT FOR CPVC PIPE

MSDS Number

BBGVP

National Stock Number

8040-00F000526

Product Name

FUSE-ON 940 SOLVENT CEMENT FOR CPVC PIPE

Manufacturer

R AND G SLOANE MANUFACTURING CO

Product Identification

Product ID:FUSE-ON 940 SOLVENT CEMENT FOR CPVC PIPE

MSDS Date:01/01/1985

FSC:8040

NIIN:00F000526

MSDS Number: BBGVP

Responsible Party

R & G SLOANE MANUFACTURING CO.

Emergency Phone: 213/ 875-0160

Cage: 08717

Contractor

R & G SLOANE MANUFACTURING COMPANY

SUN VALLEY, CA 91353

US

(818) 767-4726

Cage: 08717

Ingredients

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

CYCLOHEXANONE (SARA III)

CAS: 108-94-1

RTECS: GW1050000

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TETRAHYDROFURAN (SARA III)

CAS: 109-99-9

RTECS: LU5950000

OSHA PEL200 PPM/250 STEL

ACGIH TLV: 200 PPM/250STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

CHLORINATED POLYVINYL CHLORIDE

RTECS: FO1930000

Hazards

Effects of Overexposure:NAUSEA, DIZZINESS, HEADACHE FROM SEVERE OVEREXPOSURE. NARCOSIS, IRRITATION OF EYES & NASAL PASSAGE

First Aid

First Aid:VAPORS: REMOVE TO FRESH AIR AND ASSIST BREATHING IF NECESSARY. SKIN: REMOVE CONTAMINATED CLOTHING AND WASH SKIN WITH WATER FOR 15 MINUTES. FLUSH EYES WITH PLENTY OF WATER AND CALL PHYSICIAN. INGESTION : DO NOT INDUCE VOMITING, CALL PHYSICIAN.

Fire Fighting

Flash Point:6F, T.O.C.

Lower Limits:1.8

Upper Limits:11.8

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM-ANSUL 'PURPLE K'

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS IN CONFINED QUARTERS

Unusual Fire/Explosion Hazard:FIRE HAZARD BECAUSE OF LOW FLASH POINT, HIGH VOLATILITY.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. AVOID BREATHING OF VAPORS. KEEP LIQUID OUT OF EYE FLUSH WITH LARGE VOLUME OF WATER. CONTAIN LIQUID WITH SAND OR EARTH. PRENT LIQUID FROM ENTERING SEWERS.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME AND OTHER SOURCES OF IGNITION. AVOID PROLONGED BREATHI OF VAPOR. USE WITH ADEQUATE VENTILATION.

Other Precautions:AVOID CONTACT WITH SKIN. STORE BETWEEN 40F AND 110F. FOLLOW PRECAUTIONARY INFORMATION GIVEN ON CONTAINER LABEL. ALL HANDLINGQUIPMENT SHOULD BE ELECTRICALLY GROUNDED.

Exposure Controls

Respiratory Protection:ORGANIC VAPOR RESPIRATOR FOR CONFINED QUARTERS

Ventilation:LOW POINT MINIMUM OF 6 AIR CHANGES PER HOUR

Protective Gloves:RUBBER OR PVA

Eye Protection:CHEMICAL SAFETY GOGGLES

Other Protective Equipment:IMPERVIOUS APRON (IF NECESSARY)

Supplemental Safety and Health

7606 CLYBOURN, SUN VALLEY, CA 91352.

Chemical Properties

Boiling Pt:B.P. Text:151F, THF

Vapor Pres:190

Vapor Density:2.49

Spec Gravity:0.968

Evaporation Rate & Reference:8.0, BUAC=1

Appearance and Odor:TAN COLOR, MEDIUM SYRUPY LIQUID, ETHERAL ODOR.

Percent Volatiles by Volume: 90

Stability

Stability Indicator/Materials to Avoid: YES

CAUSTICS, AMMONIA, INORGANIC ACIDS, CHLORINATED COMPOUNDS

Stability Condition to Avoid: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME

Conditions to Avoid Polymerization: ALSO AVOID STRONG OXIDANTS,
ISOCYANATES.

Disposal

Waste Disposal Methods: INCINERATE. EXCESSIVE QUANTITIES SHOULD NOT BE
PERMITTED TO ENTER DRAINS. CONSULT DISPOSAL EXPERT. FOLLOW LOCAL,
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.