

## **FUSE-ON 925 SOLVENT CEMENT FOR PVC PIPE**

### **MSDS Number**

BBGVS

### **National Stock Number**

8040-00F000529

### **Product Name**

FUSE-ON 925 SOLVENT CEMENT FOR PVC PIPE

### **Manufacturer**

R AND G SLOANE MANUFACTURING

### **Product Identification**

Product ID:FUSE-ON 925 SOLVENT CEMENT FOR PVC PIPE

MSDS Date:01/01/1985

FSC:8040

NIIN:00F000529

MSDS Number: BBGVS

### **Responsible Party**

R & G SLOANE MANUFACTURING

Emergency Phone: 213/ 875-0160

Cage: 08717

### **Contractor**

R & G SLOANE MANUFACTURING COMPANY

SUN VALLEY, CA 91353

US

(818) 767-4726

Cage: 08717

### **Ingredients**

PVC RESIN, POLYVINYL CHLORIDE

RTECS: KV0350000

TETRAHYDROFURAN (SARA III)

CAS: 109-99-9

RTECS: LU5950000

OSHA PEL200 PPM/250 STEL

ACGIH TLV: 200 PPM/250STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

CYCLOHEXANONE (SARA III)

CAS: 108-94-1

RTECS: GW1050000

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Effects of Overexposure: NAUSEA, DIZZINESS, HEADACHE; NARCOSIS, IRRITATION TO EYES AND NASAL PASSAGES.

## First Aid

First Aid: VAPORS: REMOVE TO FRESH AIR, ASSIST BREATHING IF NECESSARY.  
SKIN: REMOVE CONTAMINATED CLOTHING, WASH SKIN WITH WATER FOR 15 MINUTES. EYES: FLUSH WITH WATER FOR 15 MINUTES, CALL PHYSICIAN.  
INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

## Fire Fighting

Flash Point: 8°F, T.O.C.  
Lower Limits: 2.0  
Upper Limits: 11.8  
Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, FOAM-ANSUL 'PURPLE K'  
Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS FOR CONFINED QUARTERS  
Unusual Fire/Explosion Hazard: FIRE HAZARD BECAUSE OF LOW FLASH POINT, HIGH VOLATILITY AND HEAVY VAPORS.

## Accidental Release

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. AVOID BREATHING OF VAPORS. KEEP LIQUID OUT OF EYES. USE WITH LARGE VOLUME OF WATER. CONTAIN LIQUID WITH SAND OR EARTH. PREVENT LIQUID FROM ENTERING SEWERS.

## Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION. AVOID PROLONGED BREATHING OF VAPOR. USE WITH ADEQUATE VENTILATION.  
Other Precautions: AVOID CONTACT WITH SKIN. STORE BETWEEN 40°F AND 110°F. FOLLOW PRECAUTIONARY INFORMATION GIVEN ON CONTAINER LABEL. ALL HANDLING EQUIPMENT SHOULD BE ELECTRICALLY GROUNDED.

## Exposure Controls

Respiratory Protection: ORGANIC VAPOR RESPIRATOR FOR CONFINED AREAS  
Ventilation: LOW POINT MINIMUM OF 6 AIR CHANGES PER HOUR  
Protective Gloves: RUBBER OR PVA  
Eye Protection: CHEMICAL SAFETY GOGGLES  
Other Protective Equipment: IMPERVIOUS APRON  
Supplemental Safety and Health  
7606 CLYBOURN, SUN VALLEY, CA 913552

## Chemical Properties

Boiling Pt: B.P. Text: 151°F, THF  
Vapor Pres: 190  
Vapor Density: 2.49  
Spec Gravity: 0.95  
Evaporation Rate & Reference: 5-8 BUAC=1  
Appearance and Odor: GRAY, MEDIUM SYRUPY LIQUID, ETHERAL ODOR  
Percent Volatiles by Volume: 90

## Stability

Stability Indicator/Materials to Avoid: YES

CAUSTICS, AMMONIA, INORGANIC ACIDS, CHLORINATED COMPOUNDS

Stability Condition to Avoid: KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME

Conditions to Avoid Polymerization: ALSO AVOID STRONG OXIDANTS, ISOCYANATES

## Disposal

Waste Disposal Methods: INCINERATE. EXCESSIVE QUANTITIES SHOULD NOT BE PERMITTED TO ENTER DRAINS. CONSULT DISPOSAL EXPERT. FOLLOW LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.