

DELTRON CATALYST, DAU2

MSDS Number

BBGVX

National Stock Number

8010-00F000533

Product Name

DELTRON CATALYST, DAU2

Manufacturer

PPG INDUSTRIES INC COATINGS AND RESINS DIV

Product Identification

Product ID:DELTRON CATALYST, DAU2

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000533

MSDS Number: BBGVX

Responsible Party

PPG INDUSTRIES, INC. COATINGS & RESINS DIVISION

Emergency Phone: 304/ 843-1300

Cage: DO894

Contractor

PPG INDUSTRIES, INC.

9

ALLISON PARK, PA 15101

US

412-592-5555

Cage: DO894

Ingredients

ISOPHORONE DIISOCYANATE (SARA III)

CAS: 4098-71-9

RTECS: NQ9370000

Fraction By Weight:

OSHA PELS 0.005PPM/0.02STEL

ACGIH TLV: 0.005 PPM; 9394

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 30%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 10%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 10%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5 - 10%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:HARMFUL IF INHALED OR ABSORBED THROUGH SKIN;
MAY CAUSE LUNG IRRITATION OR ALLERGIC REACTION

First Aid

First Aid:VAPOR: REMOVE TO FRESH AIR. IF BREATHING DIFFICULTY PERSISTS,
CONSULT PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR
15 MINUTES. CALL A PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP &
WATER.

Fire Fighting

Flash Point:24 F, PMCC

Lower Limits:2.1

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE USED TO COOL CLOSED
CONTAINERS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME TEMPERATURES.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITHNERT ABSORBENT AND
NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE CLASS

IB FLAMMABLE LIQUIDS.

Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT FLAME CUT, BRAZE OR WELD WITHOUT APPROVED RESPIRATORS.

Exposure Controls

Respiratory Protection:POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves:REQUIRED

Eye Protection:REQUIRED

Other Protective Equipment:IMPERVIOUS CLOTHING

Supplemental Safety and Health

ONE GATEWAY CENTER - PITTSBURGH, PA 15222. PRODUCT ALSO CONTAINS POLYMERIC ISOCYANATE (20%), ETHYL ACETATE (15%), ALIPHATIC HYDROCARBON (10%).

Chemical Properties

Boiling Pt:B.P. Text:75-156PPM

Vapor Density:>AIR

Evaporation Rate & Reference:< ETHER

Percent Volatiles by Volume:85

Stability

Stability Indicator/Materials to Avoid:YES

WATER, ALCOHOLS, AND STRONG BASES

Hazardous Decomposition Products:CARBON DIOXIDE, HYDROGEN CYANIDE, ISOPHORONE DIISOCYANATE

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.