

## **1614 KRYLON HIGH HEAT SPRAY PAINT**

### **MSDS Number**

BBGWJ

### **National Stock Number**

8010-00F000542

### **Product Name**

1614 KRYLON HIGH HEAT SPRAY PAINT

### **Manufacturer**

BORDEN INC

### **Product Identification**

Product ID:1614 KRYLON HIGH HEAT SPRAY PAINT

MSDS Date:11/25/1985

FSC:8010

NIIN:00F000542

MSDS Number: BBGWJ

### **Responsible Party**

BORDEN INC

180 E BROAD STREET

COLUMBUS , OH 43215

Emergency Phone: (614) 457-5200

Info Phone: (614) 457-5200

Cage: 07982

### **Contractor**

KRYLON PRODUCTS

OLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

### **Ingredients**

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 34-37%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 30-36%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

PROPANE  
CAS: 74-98-6  
RTECS: TX2275000  
Fraction By Weight: 18%  
OSHA PEL1000 PPM  
ACGIH TLV: ASPHYXIAN; 9192

XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS: 1330-20-7  
RTECS: ZE2100000  
Fraction By Weight: 7%  
OSHA PEL100 PPM/150 STEL  
ACGIH TLV: 100 PPM/150STEL;9192  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

N-BUTYL ALCOHOL (SARA III)  
CAS: 71-36-3  
RTECS: EO1400000  
Fraction By Weight: 0.5%  
OSHA PEL100 PPM  
ACGIH TLV: S, C 50 PPM; 9293  
EPA Report Quantity: 5000 LBS  
DOT Report Quantity: 5000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: CENTRAL NERVOUS SYSTEM  
DEPRESSION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS,  
ASPHYXIATION, CYANOSIS, RESPIRATORY DISTRESS, DROWSINESS, HARMFUL,  
& IRRITATION OF NOSE, THROAT, & LUNGS. SKIN/EYES: IRRITATION.  
INGESTION: HARMFUL.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION,  
HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS,  
ASPHYXIATION, CYANOSIS, RESPIRATORY DISTRESS, DROWSINESS, HARMFUL,  
& IRRITATION OF NOSE, THROAT, & LUNGS, LIVER & KIDNEY DAMAGE.  
SKIN/EYES: IRRITATION. INGESTION: HARMFUL.

## First Aid

First Aid:INGESTION: DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH  
AIR. SKIN/EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. OBTAIN  
MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO HIGH TEMPS MAY CAUSE BURSTING. DON'T PUNCTURE/INCINERATE CONTAINER. DON'T SPRAY NEAR OPEN FLAME.

## Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. SOAK UP WITH ABSORBENT MATERIAL. VENTILATE AREA. REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

## Handling

Handling and Storage Precautions:DON'T STORE AT TEMPERATURES >120F. CONTENTS UNDER PRESSURE & EXPOSURE TO HIGH TEMPERATURE MAY CAUSE BURSTING. DON'T SPRAY NEAR OPEN FLAME.

Other Precautions:DON'T CUT, PUNCTURE, OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY. AVOID BREATHING VAPOR OR MIST. USE W/ADEQUATE VENTILATION. AVOID CONTACT W/SKIN & EYES.

## Exposure Controls

Respiratory Protection:APPROVED RESPIRATORY PROTECTION IS REQUIRED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.

Ventilation:PROVIDE ADEQUATE VENTILATION TO KEEP Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES, FACE SHIELD, SAFETY GLASSES

Other Protective Equipment:SAFETY SHOES, HARD HATS, & SUITABLE CLOTHING.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

## Chemical Properties

Vapor Pres: 60 PSIG

Vapor Density:>AIR

Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC

Solubility in Water:SLIGHT

Appearance and Odor:BLACK

Percent Volatiles by Volume: 89/WT

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH TEMPERATURES >120, HEAT SOURCE, DIRECT SUNLIGHT, OPEN FLAME, RADIATORS, STOVES, & OTHER IGNITION SOURCES.

Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. EMPTY CONTAINER MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.