

SPARVAR BRILL DEC. METALLIC S-121 TO S-123

MSDS Number

BBGWK

National Stock Number

8010-00F000543

Product Name

SPARVAR BRILL DEC. METALLIC S-121 TO S-123

Manufacturer

BORDEN INC KRYLON DEPARTMENT

Product Identification

Product ID: SPARVAR BRILL DEC. METALLIC S-121 TO S-123

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00F000543

MSDS Number: BBGWK

Responsible Party

BORDEN, INC., KRYLON DEPARTMENT

Emergency Phone: 215/278-2400

Cage: EO430

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 8-10%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 16%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150 STEL; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 36%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ACRYLIC ESTER RESIN

Fraction By Weight: 5-6%

ACGIH TLV: .

COPPER OR BRASS FLAKE (SEE SUPPLEMENTAL SECTION FOR

RTECS: BL5325000

Fraction By Weight: 4-6%

ACGIH TLV: .

Hazards

Effects of Overexposure:DIZZINESS, CONFUSION, WEAKNESS.

First Aid

First Aid:GET FRESH AIR. IF SPRAYED IN EYES, WASH WITH WATER 15 MINUTES.

Fire Fighting

Flash Point:N.A.

Extinguishing Media:TREAT AS SOLVENT FIRES--CLASS B

Fire Fighting Procedures:CAN MAY BURN LIKE A BLOWTORCH; RELEASE SPRAY BUTTON TO EXTNG

Unusual Fire/Explosion Hazard:IF CAN IS IN FIRE, CAN MAY BURST WITH VIOLENCE; THIS WILL RELEASE ITS FLAMMABLE CONTENT

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. SOAK UP WITH ABSORBENT MATERIAL. VENTILATE AREA.

Handling

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES OVER 120 F. CONTENTS UNDER PRESSURE AND EXPOSURE TO HIGH TEMPERATE MAY CAUSE BURSTING.

Other Precautions:AVOID HEAT SOURCES. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY. AVOID INCINERATION OR USE ONLY A STRONG, CLOSED COAINER. AVOID PUNCTURING.

Exposure Controls

Respiratory Protection:VENTILATE ADEQUATELY.

Ventilation:SUPPLEMENT NATURAL VENTILATION AS NECESSARY FOR TLV'S

Protective Gloves:NOT NEEDED

Eye Protection:DESIRABLE; NOT MANDATORY

Supplemental Safety and Health

FORD & WASHINGTON STS., NORRISTOWN, PA 19404. PRODUCT ALSO CONTAINS PROPANE/ISOBUTANE (28%).

Chemical Properties

Boiling Pt:B.P. Text:N.A.

Vapor Pres:N.A

Vapor Density:>1

Spec Gravity:Evaporation Rate & Reference:>1, BUAC=1

Solubility in Water:SLIGHT

Percent Volatiles by Volume: 88

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:BURNING SPRAY MAY PRODUCE TOXIC AND IRRITATING COMPOUNDS

Disposal

Waste Disposal Methods:WHEN DRY, DISCARD AS NON-DANGEROUS TRASH TO BE BURIED OR BURNED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.