

P.F. INT. ACRYLIC WALL FINISH, 202-10

MSDS Number

BBGWL

National Stock Number

8010-00F000544

Product Name

P.F. INT. ACRYLIC WALL FINISH, 202-10

Manufacturer

O'BRIEN CORP FULLER O'BRIEN PAINTS

Product Identification

Product ID:P.F. INT. ACRYLIC WALL FINISH, 202-10

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000544

MSDS Number: BBGWL

Responsible Party

O'BRIEN CORPORATION, FULLER O'BRIEN PAINTS

Cage: 85207

Contractor

O'BRIEN CORPORATION, FULLER O'BRIEN PAINTS

SOUTH SAN FRANCISCO, CA 94080-6207

US

Cage: 85207

Ingredients

AMMONIA (SARA III)

CAS: 7664-41-7

RTECS: BO0875000

Fraction By Weight:

OSHA PEL50 PPM

ACGIH TLV: 25 PPM/35 STEL; 9293

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

BUTYL CARBITOL

CAS: 112-34-5

RTECS: KJ9100000

Fraction By Weight:

ACGIH TLV: 50PPM

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure:EYES: PRIMARY IRRITATION. INHALATION: MAY CAUSE HEADACHE AND NAUSE. SKIN: POSSIBLE PRIMARY IRRIT.

First Aid

First Aid:EYES: OBTAIN MEDICAL ATTENTION IMMEDIATELY. FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MINUTES. INGESTION: OBTAIN MEDICAL ATTENTION IMMEDIATELY. INHALATION: REMOVE FROM AREA TO FRESH AIR. RESTORE BREATHING. SKIN: WASH WITH SOAP & WATER.

Fire Fighting

Unusual Fire/Explosion Hazard:CLOSED CONTAINER MAY BUILD UP PRESSURE WHEN EXPOSED TO HEAT.

Accidental Release

Spill Release Procedures:SOAK UP AND REMOVE WITH ABSORBENT AND INERT MATERIAL. PROVIDE ADEQUATE VENTILATION.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING.
Other Precautions:DO NOT INGEST. KEEP OUT OF THE REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:USE RESPIRATOR OR PARTICLE MASK TO AVOID BREATHING SPRAY MIST.
Ventilation:SUFFICIENT TO KEEP BELOW LEL AND TLV'S.
Eye Protection:GOGGLES
Other Protective Equipment:PROTECTIVE OVERALLS RECOMMENDED.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212-455F
Vapor Density:Evaporation Rate & Reference:< ETHER
Percent Volatiles by Volume: 66

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.