

VERSATEC PREMIX

MSDS Number

BBGWT

National Stock Number

3610-00F000551

Product Name

VERSATEC PREMIX

Manufacturer

HILORD CHEMICAL CORP

Product Identification

Product ID:VERSATEC PREMIX

MSDS Date:01/01/1985

FSC:3610

NIIN:00F000551

MSDS Number: BBGWT

Responsible Party

HILORD CHEMICAL CORPORATION

Emergency Phone: 713/ 656-3424

Cage: 1EV20

Contractor

HILORD CHEMICAL CORP

HAUPPAUGE, NY 11788-4004

US

516-234-7373

Cage: 1EV20

Ingredients

PIGMENTS

Fraction By Weight: 0.7%

RESIN

Fraction By Weight: 0.5%

ISOPAR G (COMPLEX MIXTURE OF PETROLEUM HYDROCARBONS)

Fraction By Weight: 98.8%

ACGIH TLV: 400PPM

Hazards

Effects of Overexposure:INHALATION OF HIGH VAPOR CONCENTRATIONS:
RESPIRATORY IRRITATION; DRYING OF SKIN IF OVEREXPOSED.

First Aid

First Aid:VAPORS: REMOVE FROM EXPOSURE IMMEDIATELY, CALL A PHYSICIAN.
IF BREATHING IS IRREGULAR CALL PHYSICIAN. SKIN: REMOVE CONTAMINATED
CLOTHING, WASH WITH SOAP & WATER. EYES: FLUSH WITH WATER UNTIL
IRRITATION SUBSIDES. IF INGESTED DO NOT INDUCE VOMITING

Fire Fighting

Flash Point:104-107F
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE
Fire Fighting Procedures:DO NOT USE WATER SPRAY OR FLOODING
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID; DO NOT STORE OR MIX
WITH STRONG OXIDANTS. FLOODING TENDS TO SPREAD BURNING LIQUI

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES. RECOVER FREE LIQUID.
ADD ABSORBENT TO SPILL AREA. AVOID BREHING VAPORS. VENTILATE
ENCLOSED SPACES. KEEP PETROLEUM PRODUCTS OUT OF PLIC SEWERS,
DITCHES, AND BODIES OF WATER.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. KEEP AWAY FROM
HEAT AND OPEN FLAME.
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. REMOVE
CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER AFTER CONTACT.

Exposure Controls

Respiratory Protection:NORMALLY NOT NEEDED IF VENTILATION IS ADEQUATE
Ventilation:LOCAL EXHAUST: > 60FPM; MECHANICAL: EXPLOSION-PROOF
Eye Protection:NORMALLY NOT NEEDED
Other Protective Equipment:OIL-IMPERVIOUS APRON
Supplemental Safety and Health
70 ENGINEERS ROAD, HAUPPAUGE, NEW YORK 11788.

Chemical Properties

Boiling Pt:B.P. Text:320-350F
Vapor Pres:2
Vapor Density:5
Spec Gravity:0.75
Evaporation Rate & Reference:0.45, -BUOAC=1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK, SLIGHTLY VISCOUS, HYDROCARBON ODOR
Percent Volatiles by Volume:98.8

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS LIKE LIQUID CHLORINE AND CONCENTRATED LIQUID
Hazardous Decomposition Products:CARBON MONOXIDE IN CASE OF INCOMPLETE
COMBUSTION

Disposal

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL
REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED DISPOSAL
SITE OF FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.