SUPER KOROPON, 519X303

MSDS Number

BBGXG

National Stock Number

8010-00F000561

Product Name

SUPER KOROPON, 519X303

Manufacturer

DESOTO INC

Product Identification

Product ID:SUPER KOROPON, 519X303
MSDS Date:01/01/1985
FSC:8010
NIIN:00F000561
MSDS Number: BBGXG

Responsible Party

DESOTO, INC.

Emergency Phone: 391-9000

Cage: 32758

Contractor

DESOTO, INC.

5030

DES PLAINES, IL 60017

US

708-391-9000

Cage: 32758

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

AROMATIC SOLVENT

Fraction By Weight:

ACGIH TLV: 100PPM

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 40%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TALC (CONTAINING NO ASBESTOS)

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight:

OSHA PEL2 MG/M3 RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9192

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 10%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

Hazards

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. NOTIFY A PHYSICIAN. SKIN: WASH AFFECTED AREAS WITH WATER. REMOVE CONTAMINATED CLOTHING. EYES: FLUSH WITH WATER FOR 15 MINUTES. INGESTION: CONSULT P HYSICIAN.

Fire Fighting

Flash Point:23.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLEIQUIDS.
Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO T SAND, OR WELD DRY COATING WITHOUT APPROVED RESPIRATOR.

Exposure Controls

Respiratory Protection:ORGANIC VAPOR RESPIRATOR; IN CONFINED AREAS USE AIR LINE TYPE RESPIR
Ventilation:GENERAL DILUTION OR LOCAL EXHAUST
Protective Gloves:BUTYL RUBBER

Eye Protection:SPLASH-PROOF
Other Protective Equipment:PROTECTIVE CLOTHING: BUTYL RUBBER APRON; WASHING FACILITIES.
Supplemental Safety and Health
1700 S. MT. PROSPECT ROAD/ DES PLAINES, ILLINOIS 60018. PRODUCT ALSO CONTAINS STRONTIUM CHROMATE PIGMENT (

Chemical Properties

Boiling Pt:B.P. Text:176-315F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:70.3

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.