

GREEN LACQUER, 600SL20668

MSDS Number

BBGXL

National Stock Number

8010-00F000565

Product Name

GREEN LACQUER, 600SL20668

Manufacturer

RED SPOT PAINT AND VARNISH CO INC

Product Identification

Product ID: GREEN LACQUER, 600SL20668

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00F000565

MSDS Number: BBGXL

Responsible Party

RED SPOT PAINT & VARNISH CO., INC.

Emergency Phone: 812/428-9100

Cage: EO503

Contractor

RED SPOT PAINT AND VARNISH CO INC

418

EVANSVILLE, IN 47703

US

800-424-9300(CHEMTREC)

Cage: 16214

Ingredients

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 50%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPYLENE GLYCOL MONOMETHYL ETHER

CAS: 107-98-2

RTECS: UB7700000

Fraction By Weight: 25%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 25%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: INHALATION: ANESTHETIC; IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid: FUMES: REMOVE FROM EXPOSURE; RESTORE BREATHING. NOTIFY A PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH RUNNING WATER FOR 15 MINUTES. TAKE TO A PHYSICIAN FOR DEFINITIVE TREATMENT. SKIN: WASH WITH WATER. REMOVE CONTAMINATED CLOTHING. CONSULT PHYSICIAN.

Fire Fighting

Flash Point: 61F, F.T.C.C.

Lower Limits: 1.4

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: WATER FOG MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY ON HOT SURFACES.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR THE STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS.

Other Precautions: DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OR LIQUID IN EXCESS OF A FEW INCHES. DO NOT FLAME CUT, BRAZE OR WELD DRY COATING W/OUT RESPIRATOR.

Exposure Controls

Respiratory Protection: FOR CONFINED AREAS, USE A BUREAU OF MINES APPROVED RESPIRATOR

Ventilation: GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves: REQUIRED

Eye Protection: SPLASH-PROOF EYEWEAR

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

110 MAIN ST./ EVANSVILLE/ IN. 47701.

Chemical Properties

Boiling Pt: B.P. Text: 94-120F

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 63.6

Stability

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: COMBUSTION FUMES MAY CONTAIN CO AND CO2/

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.