

KENNEDY BROWN WRINKLE

MSDS Number

BBGXM

National Stock Number

8010-00F000566

Product Name

KENNEDY BROWN WRINKLE

Manufacturer

SEYMOUR OF SYCAMORE INC

Product Identification

Product ID:KENNEDY BROWN WRINKLE

MSDS Date:01/01/1985

FSC:8010

NIIN:00F000566

MSDS Number: BBGXM

Responsible Party

SEYMOUR OF SYCAMORE, INC.

Emergency Phone: 815/ 895-9101

Cage: 59581

Contractor

SEYMOUR OF SYCAMORE

SYCAMORE, IL 60178-1343

US

815-895-9101/800-255-3924

Cage: 59581

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 1.3%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 7.5%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

HEXANE (N-HEXANE)

CAS: 110-54-3

RTECS: MN9275000

Fraction By Weight: 16.5%

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

MINERAL SPIRITS

RTECS: SE7550000

Fraction By Weight: 6.5%

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 4.2%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

Hazards

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTOREBREATHING, NOTIFY PHYSICIAN. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. TAKE TO PHYSICIAN FOR DEFINITIVE TREATMENT. SKIN: REMOVE WITH SOAP AND WATER, REMOVE C ONTAMINATED CLOTHING.

Fire Fighting

Flash Point:AEROSOL -10F.

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER FOG MAY BE USED TO COOL CONTAINERS.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS, VENTILATE AREA.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

Exposure Controls

Respiratory Protection:AVOID CONTINUOUS BREATHING OF VAPORS AND SPRAY MIST

Ventilation:USE WITH ADEQUATE VENTILATION

Supplemental Safety and Health

ALSO CONTAINS 1.3% ISOPROPYL ALCOHOL TLV-400PPM. 11% PROPANE, 11% ISOBUTANE.

Chemical Properties

Boiling Pt:B.P. Text:NA
Vapor Density:>AIR
Evaporation Rate & Reference:FASTER THAN ETHER
Percent Volatiles by Volume:85

Stability

Stability Indicator/Materials to Avoid:YES
NA
Hazardous Decomposition Products:MAY PRODUCE CARBON MONOXIDE FUMES WHEN
HEATED TO COMBUSTION.

Disposal

Waste Disposal Methods:DO NOT INCINERATE AEROSOL, DISPOSE OF IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.