



SD 36118 GUNSHIP GRAY, 822X339

MSDS Number

BBGXS

National Stock Number

8010-01-100-9094

Product Name

SD 36118 GUNSHIP GRAY, 822X339

Manufacturer

DESOTO INC

Product Identification

Product ID:SD 36118 GUNSHIP GRAY, 822X339

MSDS Date:01/01/1985

FSC:8010

NIIN:01-100-9094

MSDS Number: BBGXS

Responsible Party

DESOTO, INC.

Emergency Phone: 312/ 391-9000

Cage: 32758

Contractor

DESOTO, INC.

5030

GARLAND, TX 75042

US

Cage: 32758

Ingredients

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 10%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 10%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS



2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 25%

OSHA PELs,100 PPM

ACGIH TLV: S, 5 PPM; 9192

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight:

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

SILICA-AMORPHOUS

RTECS: VV7320000

Fraction By Weight: 15%

ACGIH TLV: 6 TOTAL

Hazards

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. NOTIFY PHYSICIAN. SKIN: WASH AFFECTED AREAS WITH WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. EYES: FLUSH WITH WATER FOR 15 MINUTES. C ONSULT A PHYSICIAN. INGESTION: CONSULT MD.

Fire Fighting

Flash Point:70F, CLOSED CUP

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLELIQUIDS. DO NOT TAKE INTERNALLY.

Other Precautions:CONTAINERS MUST BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT SAND, FLAME CUT, BRAZER WELD DRY COATING WITHOUT NIOSH APPROVED RESPIRATOR.

Exposure Controls

Respiratory Protection:NIOSH APPROVED AIR LINE TYPE RESPIRATOR.

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves:BUTYL RUBBER



Eye Protection:SPLASH PROOF GOGGLES
Other Protective Equipment:BUTYL, NEOPRENE OR NITRILE RUBBER APRON
ACCEPTABLE
Supplemental Safety and Health
1700 S. MT. PROSPECT RD./ DES PLAINES ILLINOIS 60018.

Chemical Properties

Boiling Pt:B.P. Text:242-313F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:57

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:PRODUCTS OF COMBUSTION OR HAZARDOUS

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.