

786 104 RED 11136 TT L 32A TYPE II

MSDS Number

BBGXT

National Stock Number

8010-00F000573

Product Name

786 104 RED 11136 TT L 32A TYPE II

Manufacturer

AMERON PROTECTIVE COATINGS

Product Identification

Product ID:786 104 RED 11136 TT L 32A TYPE II MSDS Date:01/01/1985 FSC:8010 NIIN:00F000573 MSDS Number: BBGXT

Responsible Party

AMERON PROTECTIVE COATINGS

201 NORTH BERRY STREET

BREA, CA 92622-1020

US

Emergency Phone: 714-529-1951

Info Phone: 714-529-1951

Cage: 0Y2E4 **Contractor**

AMERON PROTECTIVE COATINGS

1020

BREA, CA 92622-1020

714-529-1951

US

Cage: 0Y2E4

Ingredients

ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL

CAS: 78-83-1 RTECS: NP9625000

Fraction By Weight: 5-15%

OSHA PEL300 MG/CUM ACGIH TLV: 152 MG/CUM

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

ETHYL BENZENE *97-3*

CAS: 100-41-4 RTECS: DA0700000



Fraction By Weight:

OSHA PEL435 MG/CUM

ACGIH TLV: 434 MG/CUM

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

ISOBUTYL ACETATE

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 23-33%

OSHA PEL150 PPM

ACGIH TLV: 713 MG/CUM

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

VM&P NAPHTHA

CAS: 78-83-1

Fraction By Weight: 17-27% EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

CELLOSOLVE ACETATE

Fraction By Weight:

ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 1-10%

OSHA PEL400 PPM ACGIH TLV: 400 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT. NERVOUS SYSTEM DEPRESSION.

SKIN/EYES: PRIMARY IRRITANT. Explanation of Carcinogenicity: NONE

 ${\tt Effects\ of\ Overexposure:} IRRITATION,\ {\tt HEADACHES},\ {\tt DIZZINESS},\ {\tt STAGGERING}$

GAIT, CONFUSION, UNCONSCIOUSNESS, COMA

First Aid

First Aid:SKIN/EYES: FLUSH W/PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC

Flash Point:30F Lower Limits:0.9

Extinguishing Media: SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: POLYMER



FOAM.

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD-UP.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DON'T STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED & PROTECTED FOR STORAGE OF FLAMMABLE LIQUIDS.

Other Precautions: DON'T TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DON'T FLAME CUT/BRAZE/WELD DRY COATING W/O RESPIRATOR.

Exposure Controls

Respiratory Protection: OUTDOOR/OPEN AREA: APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE AIR BORNE PARTICLES OF OVERSPRAY. RESTRICTED AREA: APPROVED CHEMICAL-MECHANICAL FILTERS DESIGNED TO REMOVE GAS/VAPORS. CONFINED AREA: APPROVED AIR TYPE RESPIRATORS/HOODS. Ventilation: GENERAL DILUTION/LOCAL EXHAUST: TO KEEP TLV OF INGREDIENTS BELOW ACCEPTABLE LIMITS.

Protective Gloves: REQUIRED

Eye Protection: SAFETY EYEWEAR W/SPLASH PROTECTION

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO

CONTAMINATED CLOTHING.

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE

REUSE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:175-329F

Vapor Density:>1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume:78

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid: FIRES, HEAT, HOT SURFACES, ELECTRICAL/STATIC/FRICTIONAL SPARKS & OTHER IGNITION SOURCES

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.