



---

## **ACRYLIC ENAMEL INTERMIX, BLUE, 99L-9710**

### **MSDS Number**

BBGYW

### **National Stock Number**

8010-00F000599

### **Product Name**

ACRYLIC ENAMEL INTERMIX, BLUE, 99L-9710

### **Manufacturer**

MARTIN SENOUR AUTOMOTIVE SALES

### **Product Identification**

Product ID: ACRYLIC ENAMEL INTERMIX, BLUE, 99L-9710

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00F000599

MSDS Number: BBGYW

### **Responsible Party**

MARTIN-SENOUR AUTOMOTIVE SALES

Emergency Phone: 216 566-2917

Cage: MART3

### **Contractor**

MARTIN-SENOUR CO THE DIV SHERWIN-WILLIAMS CO

CHICAGO, IL 60608-5724

US

216-566-2902

Cage: 16772

### **Ingredients**

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: DE3030000

Fraction By Weight:

OSHA PEL100 PPM

O-XYLENE (O-DIMETHYLBENZENE) (SARA III)

CAS: 95-47-6

RTECS: ZE2450000

Fraction By Weight: 40%

OSHA PEL100PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHYL BENZENE (SARA III)

CAS: 100-41-4



RTECS: DA0700000

Fraction By Weight:

OSHA PEL100 PPM/125 STEL

ACGIH TLV: 100 PPM/125STEL 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight:

OSHA PEL100 PPM

## Hazards

Effects of Overexposure:ACUTE:IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC.

## First Aid

First Aid:IN INHALED: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. IF ON SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRY BEFORE RE-USE. IF IN EYES: FLUSH EYES WITH LARGE AMOUNTS

## Fire Fighting

Flash Point:50F PMCC

Lower Limits:0.5

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAME

Unusual Fire/Explosion Hazard:SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP AREA VENTILATE-DON'T SMOKE-EXTINGUISH ALL FLA, PILOT LIGHTS AND HEATERS.

Other Precautions:USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. WASH HANDS AFTER SING.

## Exposure Controls



Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS

Ventilation: LOCAL EXHAUST PREFERABLE.

Protective Gloves: WEAR GLOVES

Eye Protection: WEAR SAFETY SPECTACLES

Supplemental Safety and Health

2-BUTOXYETHANOL (NIOSH #KJ8575000) (KJ8925000)

## Chemical Properties

Boiling Pt: B.P. Text: 222-395F

Vapor Density: YES

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 61.5

## Stability

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: CARBON DIOXIDE, MONOXIDE, OXIDES OF NITROGEN, OF HYDROGEN

## Disposal

Waste Disposal Methods: INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.