

NO. 615 H.D. PAINT & GSKT. CEMENT REMOVER

MSDS Number

BBGYX

National Stock Number

6810-00F000600

Product Name

NO. 615 H.D. PAINT & GSKT. CEMENT REMOVER

Manufacturer

SPRAYON PRODUCTS

Product Identification

Product ID:NO. 615 H.D. PAINT & GSKT. CEMENT REMOVER

MSDS Date:01/01/1985

FSC:6810

NIIN:00F000600

MSDS Number: BBGYX

Responsible Party

SPRAYON PRODUCTS

Emergency Phone: 216 292-7400

Cage: 09800

Contractor

SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

BEDFORD HEIGHTS, OH 44146

US

216-292-7400 OR 216-595-8634

Cage: 09800

Ingredients

ISOBUTANE-PROPELLANT 50% BLEND

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 15%

ACGIH TLV: 1000 PPM

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIA NT; 9192

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight:

OSHA PEL100 PPM

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 10%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 65 - 75%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:IN A CONFINED AREA VAPORS IN HIGH CONCENTRATIONS ARE ANESTHETIC.

First Aid

First Aid:BREATHING: REMOVE PATIENT TO FRESH AIR. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. SWALLOWING: CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

Fire Fighting

Flash Point:20F T.O.C.

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:DO NOT SPRAY NEAR OPEN FLAME. KEEP AT ROOM AT TEMPERATURE.

Unusual Fire/Explosion Hazard:WATER MAY BE INEFFECTIVE-WATER MAY BE USED TO USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE. AVOID BREATHING VAPORS AND REMOVE WITH INT ABSORBENT.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEATAY CAUSE BURSTING.

Other Precautions:DO NOT PUNCTURE OR INCINERATE. DO NOT SPRAY NEAR FIRE OR OPEN FLAME. KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection:AVOID BREATHING OF VAPOR OR SPRAY MIST.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV.

Protective Gloves:PROLONGED

Eye Protection:WEAR SAFETY GLASSES

Supplemental Safety and Health

SPRAYON PRODUCTS. DIV. OF SHERWIN-WILLIAMS CO. 26300 FARGO AVENUE.

BEDFORD HTS., OH 44146

Chemical Properties

Boiling Pt:B.P. Text:BELOW 0F.
Evaporation Rate & Reference:FASTER
Percent Volatiles by Volume:95%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:DO NOT STORE ABOVE 120F.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE
HYDROGEN CHLORIDE.

Disposal

Waste Disposal Methods:DO NOT INCINERATE: DISPOSE IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.