

ACRYLIC ENAMEL REDUCER, RESULAR #8831

MSDS Number

BBGYY

National Stock Number

8010-00F000601

Product Name

ACRYLIC ENAMEL REDUCER, RESULAR #8831

Manufacturer

MARTIN SENOUR AUTOMOTIVES SALES

Product Identification

Product ID: ACRYLIC ENAMEL REDUCER, RESULAR #8831

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00F000601

MSDS Number: BBGYY

Responsible Party

MARTIN-SENOUR AUTOMOTIVES SALES

Emergency Phone: 216 566-2917

Cage: MART3

Contractor

MARTIN-SENOUR CO THE DIV SHERWIN-WILLIAMS CO

CHICAGO, IL 60608-5724

US

216-566-2902

Cage: 16772

Ingredients

O-XYLENE (O-DIMETHYLBENZENE) (SARA III)

CAS: 95-47-6

RTECS: ZE2450000

Fraction By Weight: 5%

OSHA PEL100PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 40%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

LIGHT ALIPHATIC HYDROCARBON SOLVENT

Fraction By Weight: 25%

ACGIH TLV: 100 PPM

2-BUTOXYETHANOL

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight: 5 - 15%

OSHA PELs, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight:

OSHA PELs, 200PPM/250STEL

ACGIH TLV: S, 200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC.

First Aid

First Aid: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. IF CONTACT WITH EYES IS MADE, FLUSH WITH COPIOUS QUANTITIES OF WATER FOR 15 MINUTES. SKIN CONTACT: WASH AFFECTED AREA WITH WATER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

Fire Fighting

Flash Point: 9F TCC

Lower Limits: 1.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED.

Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. DURING USE AND UNTIL ALL VAPORS ARE GONE: KEEP ARE VENTILATED- DO NOT SMOKE EXTINGUISH ALL FLAMES.

Exposure Controls

Respiratory Protection: IF ENGINEERING CONTROLS OF AIR CONTAMINANTS ARE NOT FEASIBLE.

Ventilation: LOCAL SPECIAL VENTILATION REQUIRED TO KEEP BELOW TLV/LEL

Protective Gloves: PROLONG

Eye Protection:SAFETY SPECTACLES
Supplemental Safety and Health
ACETONE-AL3150000, 15%, 750 PPM. MARTIN-SENOUR AUTOMOTIVE SALES 5422
DANSHER ROAD. COUNTRYSIDE, ILLINOIS 60525

Chemical Properties

Boiling Pt:B.P. Text:132-340F
Vapor Density:YES
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:100.

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.