

## **8424,VPI 750 FLOORING ADHESIVE**

### **MSDS Number**

BBHFZ

### **National Stock Number**

8040-00F000736

### **Product Name**

8424,VPI 750 FLOORING ADHESIVE

### **Manufacturer**

GIBSON HOMANS CO

### **Product Identification**

Product ID:8424,VPI 750 FLOORING ADHESIVE

MSDS Date:05/22/1992

FSC:8040

NIIN:00F000736

MSDS Number: BBHFZ

### **Responsible Party**

GIBSON HOMANS CO

1101 HANZLIK AVE

BALTIMORE , MD 21237

US

Emergency Phone: 216-843-2982

Info Phone: 410-391-4500

Cage: GIBS1

### **Contractor**

GIBSON HOMANS CO

BALTIMORE, MD 21237-5000

US

410-391-4500/216-843-2982

Cage: GIBS1

### **Ingredients**

ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 2-4%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM

AROMATIC PETROLEUM DISTILLATE, HEAVY STRAIGHT RUN NAPHTHA C

CAS: 64741-41-9

Fraction By Weight:

METHANOL (METHYL ALCOHOL), COLUMBIAN SPIRITS

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 6-10%  
OSHA PELs,200PPM/250STEL  
ACGIH TLV: S,200PPM/250STEL; 93  
EPA Report Quantity: 5000 LBS  
DOT Report Quantity: 5000 LBS

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 1-5%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: DIZZINESS, HEADACHE,  
UNCONSCIOUSNESS, IRRITATION TO RESPIRATORY TRACT IRRITATION.  
SKIN/EYES: IRRITATION.  
Explanation of Carcinogenicity:NONE  
Medical Cond Aggravated by Exposure:SKIN & LUNG DISORDERS

## First Aid

First Aid:EYES: FLUSH W/WATER FOR AT LEAST 15 MINS. SKIN: WASH W/SOAP &  
WATER. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. KEEP  
INDIVIDUAL CALM. INGESTION: TREAT SYMPTOMATICALLY. OBTAIN MEDICAL  
ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:84F  
Lower Limits:6.7%  
Upper Limits:36%  
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. USE WATER TO  
COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD  
UP/AUTO-IGNITION/EXPLOSION. FOG NOZZLES ARE PREFERABLE.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT. DON'T USE IN VICINITY OF OPEN FLAME OR  
SPARKS. FLAMMABLE SOLID.

## Accidental Release

Spill Release Procedures:SCRAPE INTO CONTAINERS FOR DISPOSAL.

## Handling

Handling and Storage Precautions:DON'T STORE >120F. KEEP AWAY FROM  
HEAT, SPARKS, & OPEN FLAME.  
Other Precautions:AVOID CONTACT W/SKIN. KEEP OUT OF REACH OF CHILDREN.

## Exposure Controls

Respiratory Protection:NONE REQUIRED W/ADEQUATE VENTILATION.  
Ventilation:AS NECESSARY TO MAINTAIN EXPOSURE BELOW TLV LEVEL  
Protective Gloves:NONE USUALLY REQUIRED  
Eye Protection:SAFETY GOGGLES  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.  
Supplemental Safety and Health

---

## Chemical Properties

Boiling Pt:B.P. Text:148F  
Vapor Pres:97  
Vapor Density:>1  
Spec Gravity:1.37  
Evaporation Rate & Reference:(BU AC = 1): >1  
Solubility in Water:INSOLUBLE  
Appearance and Odor:BROWN MASTIC W/MILD ALCOHOL ODOR.  
Percent Volatiles by Volume:22%

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:OPEN FLAME, SPARKS, OR OTHER SOURCES OF IGNITION.  
Hazardous Decomposition Products:CO & ORGANIC COMPOUNDS OF UNKOWN STRUCTURE.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. FLAMMABLE SOLID. RCRA HAZARDOUS WASTE NO: D001. DOT UN1133. REPORTABLE QUANTITY: >50,000 LBS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.