

### **MICCROSTOP**

### **MSDS Number**

**BBHGR** 

#### **National Stock Number**

8010-00F000762

#### **Product Name**

**MICCROSTOP** 

#### Manufacturer

TOLBER DIV PYRAMID PLASTICS INC

#### **Product Identification**

Product ID: MICCROSTOP MSDS Date:01/16/1986 FSC:8010 NIIN:00F000762

MSDS Number: BBHGR

# **Responsible Party**

TOLBER DIV/PYRAMID PLASTICS, INC.

220 W. 5TH STREET HOPE, AK 71801

Emergency Phone: (501) 777-3251

Info Phone: (501) 777-3251

Cage: EO532 **Contractor** 

TOLBER DIV/PYRAMID PLASTICS, INC.

HOPE, AK 71801

US

(501) 777-3251

Cage: EO532

## **Ingredients**

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3 RTECS: EL6475000

Fraction By Weight: 68-71%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

PROPYLENE OXIDE (SARA III)

CAS: 75-56-9

RTECS: TZ2975000 Fraction By Weight: 4%

OSHA PEL100 PPM



ACGIH TLV: 20 PPM; 9293
EPA Report Quantity: 100 LBS
DOT Report Quantity: 100 LBS

VINYL CHLORIDE/VINYL ACETATE/MALEIC ANHYDRIDE

CAS: 25085-82-9

Fraction By Weight: 21-24%

**RED DYE** 

CAS: 98903-68-7

Fraction By Weight: 0.5%

#### Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: NAUSEA & LIGHT HEADINESS.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: NAUSEA & LIGHT HEADINESS.

#### First Aid

FIRST AID: SKIN: WASH W/WATER. INGESTION: DRINK WATER & INDUCE VOMITING.

EYES: FLUSH W/WATER.

## Fire Fighting

Flash Point Method:TCC

Flash Point:1F

Extinguishing Media:CO2 Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard: MATERIAL IS HIGHLY VOLATILE & CAN BE

IGNITED BY FLAMES, SPARKS, OR HEAT.

#### **Accidental Release**

Spill Release Procedures: WIPE UP W/ABSORBENT MATERIAL. KEEP AWAY FROM FLAME OR SPARKS.

#### Handling

Handling and Storage Precautions: STORE AWAY FROM HEAT, FLAMES & SPARKS.

#### **Exposure Controls**

Respiratory Protection: NONE NEEDED IF AREA IS VENTILATED Ventilation: LOCAL EXHAUST: EXHAUST KETONE FUMES

Eye Protection: GOGGLES
Supplemental Safety and Health

### **Chemical Properties**

Boiling Pt:B.P. Text:118F Vapor Density:2.8 Spec Gravity:0.95

Evaporation Rate & Reference:(BU AC = 1): 5 Appearance and Odor:RED LIQUID W/KETONE ODOR.

Percent Volatiles by Volume:84%

#### Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS

Stability Condition to Avoid: SPARKS, FLAMES & HEAT

Hazardous Decomposition Products: HYDROGEN CHLORIDE, CO

### **Disposal**



Waste Disposal Methods:DISPOSAL MUST, BE CARRIED OUT IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS FOR FLAMMABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.