

## **SEALTIGHT #164 JOINT SEALER**

### **MSDS Number**

BBHJT

### **National Stock Number**

8030-00F000808

### **Product Name**

SEALTIGHT #164 JOINT SEALER

### **Manufacturer**

W R MEADOWS INC

### **Product Identification**

Product ID:SEALTIGHT #164 JOINT SEALER

MSDS Date:10/01/1985

FSC:8030

NIIN:00F000808

MSDS Number: BBHJT

### **Responsible Party**

W.R. MEADOWS, INC.

ELGIN , IL 60121

Emergency Phone: (312) 683-4500

Info Phone: (312) 683-4500

Cage: EO540

### **Contractor**

W.R. MEADOWS, INC.

543

ELGIN, IL 60121

US

(312) 683-4500

Cage: EO540

### **Ingredients**

ASPHALT (PETROLEUM)

CAS: 8052-42-4

RTECS: CI9900000

ACGIH TLV: 5 MG/M3; (FUME);9192

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: HEATED MATERIAL MAY CAUSE THERMAL BURNS. INHALATION: EYE/RESPIRATORY IRRITATION & UNCONSCIOUSNESS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: HEATED MATERIAL MAY CAUSE THERMAL BURNS.

INHALATION: EYE/RESPIRATORY IRRITATION & UNCONSCIOUSNESS.

### **First Aid**

First Aid:SKIN: REMOVE/WASH WITH SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINUTES. INHALATION: REMOVE PERSON TO FRESH AIR & TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION AS REQUIRED.

---

## Fire Fighting

Flash Point Method:TOC

Flash Point:485F

Extinguishing Media:FOG, FOAM, DRY CHEMICAL, CO2

Fire Fighting Procedures:USE PETROLEUM FIRE FIGHTING PROCEDURES.

Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:COLLECT & DISPOSE OF PROPERLY. ALLOW TO COOL & SHOVEL INTO WASTE CONTAINER.

## Handling

Handling and Storage Precautions:NONE

Other Precautions:NONE

## Exposure Controls

Respiratory Protection:IN INADEQUATELY VENTILATED AREAS. USE A

NIOSH/MSHA APPROVED RESPIRATORS.

Ventilation:LOCAL EXHAUST: USE IN WELL VENTILATED AREA/AS REQUIRED TO

KEEP Protective Gloves:CHEMICAL RESISTANT

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING/LONG SLEEVES.

Supplemental Safety and Health

## Chemical Properties

Spec Gravity:1.07

Solubility in Water:NEGLIGIBLE

Appearance and Odor:ASPHALT ODOR, BLACK SOLID.

Percent Volatiles by Volume:0%

## Stability

Stability Indicator/Materials to Avoid:YES

## Disposal

Waste Disposal Methods:ANY DISPOSAL METHOD. PERMITTED WASTE DISPOSAL FACILITY. CONSULT LOCAL ORDINANCE FOR COMPLIANCE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.