
TRIG-A-CAP MARKING PAINT RED TACAPR1

MSDS Number

BBHJW

National Stock Number

8010-00F000810

Product Name

TRIG-A-CAP MARKING PAINT RED TACAPR1

Manufacturer

FOX VALLEY SYSTEMS INC

Product Identification

Product ID:TRIG-A-CAP MARKING PAINT RED TACAPR1

MSDS Date:07/17/1989

FSC:8010

NIIN:00F000810

MSDS Number: BBHJW

Responsible Party

FOX VALLEY SYSTEMS, INC.

640 INDUSTRIAL DRIVE

CARY , IL 60013-1948

Emergency Phone: (708) 639-5744

Info Phone: (708) 639-5744

Cage: 61527

Contractor

FOX VALLEY SYSTEMS, INC.

CARY, IL 60013-1948

(708) 639-5744

Cage: 61527

Ingredients

BUTANE

CAS: 106-97-8

RTECS: EJ4200000

Fraction By Weight: 10-15%

OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192

2-BUTOXYETHANOL

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight: 2-5%

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

MOLYBDATE ORANGE

CAS: 12656-85-8
RTECS: QA4660000
Fraction By Weight: 5-7%
OSHA PEL5 MG/CUM
ACGIH TLV: 5 MG/CUM

PROPANE
CAS: 74-98-6
RTECS: TX2275000
Fraction By Weight: 10-15%
OSHA PEL1000 PPM
ACGIH TLV: ASPHYXIAN; 9192

TOLUENE (SARA III)
CAS: 108-88-3
RTECS: XS5250000
Fraction By Weight: 15-30%
OSHA PEL200 PPM/150 STEL
ACGIH TLV: 50 PPM; 9293
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA
CAS: 64742-89-8
Fraction By Weight: 5-12%

XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS: 1330-20-7
RTECS: ZE2100000
Fraction By Weight: 3-10%
OSHA PEL100 PPM/150 STEL
ACGIH TLV: 100 PPM/150STEL;9192
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION, REDNESS, TEARING, BLURRED VISION, & CONJUNCTIVITIS. SKIN: MODERATE IRRITATION, DEFATTING, & DERMATITIS. INHALATION: HEADACHES, NAUSEA, DROWSINESS, IRRITATION OF THE MUCOUS MEMBRANE OF NOSE & THROAT, RESPIRATORY IRRITATION, & ALLERGIC REACTION.
Explanation of Carcinogenicity:MOLYBDATE ORANGE IS CONSIDERED TO BE A SUSPECT CARCINOGEN.
Effects of Overexposure:INGESTION: DRIED FILM OF PAINT MAY BE HARMFUL/FATAL & MAY CAUSE LEAD POISONING. INHALATION: SPRAY

MIST/SANDING DUST MAY CAUSE SEVERE BODILY HARM. EYES: IRRITATION, REDNESS, TEARING, BLURRED VISION, & CONJUNCTIVITIS. SKIN: DERMATITIS, MODERATE IRRITATION, & DEFATTING.

Medical Cond Aggravated by Exposure:ALLERGIC REACTION, DERMATITIS

First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. INGESTION: DRINK 1 OR 2 GLASSES OF WATER & INDUCE VOMITING. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES IF REQUIRED.

Fire Fighting

Flash Point:-28F

Lower Limits:1.9%

Upper Limits:8.5%

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:PREVENT PRESSURE

BUILD-UP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT. SPRAY

MIST/VAPORS FROM ONE CAN PER 400 CU FT OF AIR MAY REACH LEL.

EXTREMELY FLAMMABLE.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. WIPE UP W/INERT MATERIAL.

Handling

Handling and Storage Precautions:CONTENTS UNDER PRESSURE. EXPOSURE TO HIGH TEMPERATURES MAY CAUSE BURSTING. DON'T INCINERATE OR PUNCTURE CAN. DON'T STORE AT TEMPS >120F.

Exposure Controls

Respiratory Protection:IF VENTILATION IS INADEQUATE, USE RESPIRATORY MASK APPROVED BY NIOSH/MESA FOR PROTECTION AGAINST SPRAY MISTS. NOT NORMALLY NEEDED IF LOCAL EXHAUST IS SATISFACTORY.

Ventilation:PROVIDE ADEQUATE LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:NOT MANDATORY

Eye Protection:RECOMMENDED

Work Hygienic Practices:PRACTICE GOOD HYGIENE, HOUSEKEEPING, & HANDLING PRACTICES WHEN WORKING W/THIS PRODUCT.

Supplemental Safety and Health

WT/GAL: 8.5-9.5 LBS.

Chemical Properties

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:RED PAINT

Percent Volatiles by Volume:70%

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT, SPARKS, RADIATOR, OPEN FLAME, DIRECT SUNLIGHT, STOVE, HIGH TEMPS >120F, SOURCES OF IGNITION

Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T INCINERATE OR PUNCTURE CAN.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.