

37038 BLACK MIL-W-5044C WALKWAY TYPE II

MSDS Number

BBHMW

National Stock Number

8010-00F000936

Product Name

37038 BLACK MIL-W-5044C WALKWAY TYPE II

Manufacturer

AKRON PAINT AND VARNISH INC

Product Identification

Product ID:37038 BLACK MIL-W-5044C WALKWAY TYPE II

MSDS Date:05/12/1984

FSC:8010

NIIN:00F000936

MSDS Number: BBHMW

Responsible Party

AKRON PAINT AND VARNISH INC

1390 FIRESTONE PARKWAY

AKRON , OH 44301-1624

US

Emergency Phone: 216-773-8911

Info Phone: 216-773-8911

Cage: 70228

Contractor

AKRON PAINT AND VARNISH INC

AKRON, OH 44301-1624

US

216-773-8911

Cage: 70228

Ingredients

V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS *97-2*

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 49.5%

ACGIH TLV: 300 PPM

MINERAL SPIRITS, PETROLEUM SPIRITS *97-2*

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 0.3%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

ASBESTOS (BULK), AMPHIBOLE, ASBESTOS FIBER, SERPENTINE

CAS: 1332-21-4

RTECS: CI6475000

Fraction By Weight: 10.7%

OSHA PEL2 FB/CC

ACGIH TLV: 2 FB/CC

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

LEAD (ANIMAL CARCINOGEN BY ACGIH, IARC CARC GROUP 2B)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 0.02%

ACGIH TLV: 0.15 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

2-BUTANONE, OXIME; METHYL ETHYL KETOXIME *97-2*

CAS: 96-29-7

RTECS: EL9275000

Fraction By Weight: 0.42%

Hazards

LD50 LC50 Mixture:ORAL LD50(RATS): 3690 MG/KG (SEE SUPP)

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:INHALATION: MAY CAUSE RESPIRATORY SYSTEM IRRITATION. SKIN/EYES: LIQUID MAY CAUSE IRRITATION.

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:IRRITATION, NAUSEA, HEADACHE, LOSS OF CONSCIOUSNESS, NARCOSIS.

First Aid

First Aid:SKIN: WASH CAREFULLY W/MINERAL SPIRITS, THEN W/SOAP & WATER.

EYES: PROMPTLY & THOROUGHLY FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF NEEDED. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:SCC

Flash Point:53F

Extinguishing Media:CO2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures:WEAR A SCBA & PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL CONTAINER.

Unusual Fire/Explosion Hazard:HEAT MAY CAUSE DISRUPTIVE PRESSURE OF CONTAINERS & FLAMMABLE VAPORS MAY FORM EXPLOSIVE MIXTURES W/AIR.

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES. DAM-UP TO LIMIT SPREADING. ABSORB ON INERT MATERIAL. VENTILATE AREA.

Handling

Handling and Storage Precautions:DON'T DROP CONTAINERS. AVOID HEAT, SPARKS & OPEN FLAME. STORE AT ROOM TEMP W/GOOD VENTILATION. GROUND

CONTAINER WHEN POURING.
Other Precautions:DON'T TAKE INTERNALLY. AVOID PROLONGED INHALATION &
BODY CONTACT. CONSULT NFPA CODE.

Exposure Controls

Respiratory Protection:WEAR AN APPROPRIATE NIOSH APPROVED RESPIRATOR
WHEN SPRAYING/APPLYING IN CONFINED AREA.
Ventilation:ADEQUATE TO MAINTAIN EXPOSURE Protective Gloves:CHEMICAL RESISTANT
Eye Protection:REQUIRED
Other Protective Equipment:SAFETY GOGGLES W/SIDE SHIELDS/FACE SHIELD,
NORMAL PROTECTIVE CLOTHING
Supplemental Safety and Health
ORAL LD50 INFORMATION IS FOR 2 BUTANONE OXIME.

Chemical Properties

Boiling Pt:B.P. Text:240-300F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:66.5

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS & ALKALINE MATERIALS.
Stability Condition to Avoid:AIR, HEAT, SPARKS, OPEN FLAMES.
Hazardous Decomposition Products:BY COMBUSTION IN RESTRICTED
ENVIRONMENT: CO & TOXIC FUMES.
Conditions to Avoid Polymerization:STORAGE OF WETTED COMBUSTIBLE
MATERIALS MAY CAUSE SPONTANEOUS COMBUSTION.

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.